

LUCAS

Coatings and Mastics For The Roofing Trade

R.M. LUCAS Co. 3211 S. Wood Street Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#1900 CLEAR BRUSHABLE SEALANT WATER-BASED

PURPOSE

Polymer based Lucas #1900 Clear Brushable Sealant is an elastomeric water-based coating intended for waterproofing fiberglass roof panels and translucent skylights.

PRODUCT DESCRIPTION

Lucas #1900 is based on 100% acrylic co-polymers. The formula is non-yellowing and will develop a tack-free finish when fully cured.

APPLICATION

Surface to be coated must be dry and free of dirt or corrosion particles. Mechanically mix product before using. Avoid entraining air in the product. All seams, fasteners and penetrations should be sealed with #1071 Acrylic Roof Cement. Apply in two coats of 1 gallon per one hundred square feet each. For best results, apply coating in one direction with the slope of the roof. Clean up wet material with soap and water.

CAUTION

Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

#1900 SPECIFICATION

Applicable Specification	NA
Viscosity ASTM D-562	125 g @ 77°F (25°C) (500 cps)
Recommended rate of application	1 gal. per 100 sq. ft
Weight per gallon	9.6 lbs.
Flash Point (TCC)	None
Container Sizes	5

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.