

PRODUCT DATA BULLETIN

#2040P 40% SILANE WATERPROOFING

PURPOSE

Lucas #2040P is a silane monomer based waterproofing treatment intended for application to alkaline surfaces such as brick, mortar, cultured stone and concrete. #2040P is not intended for use on some types of natural stone. Applications of #2040P will not change the appearance of masonry or concrete. Lucas #2040P is easier to remove from glass than siloxane based treatments.

PRODUCT DESCRIPTION

Lucas #2040P is manufactured from silanes specifically suited for waterproofing applications. Small molecule size allows for effective penetration of higher density materials. Silanes react with moisture in an alkaline environment to form hydroxy groups that produce a hydrophobic water repellent surface. This product is supplied in a petroleum solvent vehicle. #2040P does not provide a visible beading effect.

APPLICATION

Mechanically mix before using. Do not store above 90°F. The surface must be clean but may be damp, although penetration will be lessened. Apply with a brush, long knap roller or an airless or garden type sprayer until the surface is fully saturated. Protect landscaping from contact with this product.

CAUTION

Combustible mixture, keep away from heat and open flame. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read MSDS prior to use.

#2040P SPECIFICATION

| | |
|--|-------------------------------|
| Applicable Specification | NA |
| Recommended rate of application | Fully saturate surface |
| %Reduction Weight Gain (21 day immersion) | 70.9 |
| Average Depth of Penetration | 3 mm |
| Weight per gallon | 7 lbs. |
| Flash Point (TCC) | +100° F |
| Container Sizes | 5, 30, 55 |

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the products suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.