

LUCAS *Coatings & Mastics for the Waterproofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#279 FORM TIE CEMENT - PREMIUM WET SURFACE

PURPOSE

Lucas #279 Form Tie Cement is an asphalt based cement intended for sealing form tie holes and other penetrations on below grade concrete and unit masonry walls. #279 will not sag or run. Formulated to adhere to damp surfaces.

PRODUCT DESCRIPTION

#279 is manufactured from refined high softening point asphalt, petroleum solvents, reinforcing fibers and a unique wet surface additive.

APPLICATION

Apply a minimum of ¼ inch thick over tie holes and 4" in diameter. The cement may be coated immediately with asphalt cutback and emulsion type dampproofing and waterproofing products. Some pressure may be required to insure adhesion to damp surfaces.

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

#279 SPECIFICATION

Applicable Specification	ASTM D 4586 Type I, Asbestos Free
Viscosity	N/A
Recommended rate of application	1/8 to 1/4 inch thick
% Asphalt	56 min
% Solids	72 min
% Non-volatile	86 max
Weight per gallon	8.5 lbs.
Flash Point (TCC)	100F + (38.7°C)
Container Sizes	5, 55

information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.