



# **LUCAS** *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 [rmlucas.com](http://rmlucas.com)

## **PRODUCT DATA BULLETIN**

**#550**

## **EZ-SEAL™ EMERGENCY ROOF PATCH**

### **PURPOSE**

Lucas #550 is a fast and effective product for temporarily stopping leaks in all types of low-slope roofs. Manufactured from gel forming bentonite clay, #550 forms a watertight barrier when exposed to water. Ideal for stopping leaks during rainstorms, in ponding areas or in winter when there is snow on the roof. Formed into free-flowing micro-pellets, Lucas #550 pours easily from the spout on its waterproof plastic container. The small pellet size exposes a greater surface area resulting in a faster gel and water stopping seal.

### **APPLICATION**

Remove the cap from the lid of the pail and pull the spout to extend it fully prior to unscrewing the cap. To seal a leak, pour the #550 over the suspected leak area 1/2 to 1 inch thick. When using as a barrier, pour in a circle around the area to be repaired as needed to block the flow of water. Remove water from inside of the circle with a wet-vac. Dry the surface and repair as necessary. #550 may also be used as a night seal. Pour onto the exposed edge of the roof to prevent moisture entry from heavy dew or unexpected rain. Sweep off and resume work when desired.

Alternate application. Lucas #550 is an excellent all-purpose absorbent. Use to contain and absorb spills of fuel, oils, coatings etc.

### **CAUTION**

Avoid breathing dust. A dust mask is recommended. Keep out of reach of children. Read MSDS prior to use.

Available in 3.5 gallon / 30 lb. and 5 gallon / 45 lb. plastic pails with re-sealable spout.

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the products suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.