



LUCAS *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#6500

UNIVERSAL™ FLASHING CEMENT

PURPOSE

Lucas #6500 Universal™ Flashing Cement is a solvent-based Terpolymer sealant intended for the repair of asphalt, modified bitumen, metal, concrete, TPO, PVC, KEE (Fibertite), Hypalon (CSPE), PIB and EPDM roofs. Extremely strong and elastic. High elongation and tensile strength insure performance under conditions that will cause asphalt based cements to fail. Unique surface active additives allow application to wet or underwater surfaces.

PRODUCT DESCRIPTION

Lucas #6500 Universal™ Flashing Cement is manufactured from synthetic elastomers, adhesive resins and polyolefin micro-fibers for reinforcement. #6500 is available in white only. Consistency is medium viscosity but high-bodied for application to vertical surfaces with no sagging.

APPLICATION

Surface must be clean and sound. Apply with a roofer's trowel 1/8 inch thick. Taper edges of the repair. Polyester fabric may be embedded for added strength. When applying to wet surfaces, pressure is required to displace moisture and insure proper adhesion. Over-application on EPDM roofs may cause swelling of the EPDM. Clean up with mineral spirits or Lucas #125 Safe-Solve Asphalt & Sealant Remover.

CAUTION

Combustible mixture, keep away from heat and open flame. Avoid prolonged contact with skin. If irritation occurs seek medical attention. Keep out of reach of children. Read MSDS prior to use.

#6500 SPECIFICATION

Recommended rate of application	1/8 inch thick
% Solids by Volume	49 min
% Non-volatile	55 max
Elongation	300% @ 77°F (25°C)
Flash Point (TCC)	+100°F (38.7°C)
Container Sizes	3.5 gallon

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully by using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the products suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.