



LUCAS *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#6900

UNIVERSAL™ CLEAR SEALANT

PURPOSE

Lucas #6900 Universal™ Clear Sealant is a high-performance, multipurpose thermoplastic elastomer based sealant. Excellent adhesion to most roof surfaces including: metal, Kynar®, asphalt, shingles, modified bitumen, EPDM, TPO, Elvaloy®/PVC, Hypalon®, vinyl, fiber cement, wood, concrete, tile, masonry, glass. #6900 is clear and will not stain if applied over asphalt products, including shingles, when applied at the recommended rate of application. Use to seal gutters, flashings and penetrations on all types of roofs. Ideal for residential roofing applications where appearance is important.

APPLICATION

Surface to be sealed must be clean. Porous surfaces may be primed with Lucas #5015 prior to application of this product. Apply with a soft bristle brush at the rate of 4 gallons per 100 sq. ft or about 1/16 of an inch thick. Please read the most current Lucas Product Data Bulletin and MSDS for this product prior to use. May be painted. Some paints may require up to one week cure time before application. Keep product warm prior to use.

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. For outdoor use only. Close fresh air intakes to avoid drawing fumes into the building. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

#6900 SPECIFICATION

Recommended rate of application	See Application
% Solids by Volume	45 min
% Non-volatile	60 max
Elongation ASTM D-412	500% @ 77°F (25°C)
Tensile Strength	1000 psi min
VOC	<550 g/l (compliant in all 50 states)
Flash Point (TCC)	+100°F (38.7°C)
Container Sizes	quart and 1 gallon cans 3 and 5 gallon pails
Standard Colors:	Clear

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the products suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.