



LUCAS *Coatings & Mastics for the Building Trades*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#7600 MODIFIED ASPHALT PAVER ADHESIVE

PURPOSE

Lucas #7600 is an economical, special purpose adhesive designed for securing concrete and natural stone pavers and cap stones. Excellent adhesion even to slightly damp surfaces. Use to secure wall cap stones and pavers applied over existing concrete or asphalt pavement. Not recommended for pool edges, risers or other areas where a fast set is desired.

PRODUCT DESCRIPTION

Lucas #7600 is manufactured from high quality asphalt binder modified with rubber elastomers.

APPLICATION

Apply 3/8 inch beads with a caulking gun 2" apart 90% of the length of the stone or paver. When applied with a trowel, use a 3/8" notched trowel. Apply to the surface and immediately embed the paver. Natural stone may require a 1/4 inch trowel. Heavier rates of application will extend the cure time.

CAUTION

Combustible liquid, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. Wear appropriate protective clothing including rubber gloves and safety goggles. A NIOSH approved respirator with organic vapor cartridges is recommended. If irritation occurs, flush with water and seek medical attention. Keep out of reach of children. Read MSDS prior to use.

#7600 SPECIFICATION

| | |
|--|---|
| Specification | NA |
| Recommended rate of application | 10-12 sq. ft. per gallon (3/8" notched trowel) |
| % Solids | 70 min |
| % Non-volatile | 78 max |
| Weight per gallon | 8.4 lbs. |
| Foot Traffic | 24-48 hours |
| Flash point (TCC) | 100° F |
| VOC | less than 300 g/l (Meets OTC, IL, OH, MI) |
| Colors | Black |
| Container sizes | 5, 55, quart tubes |

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.