



LUCAS *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

775 ALL-WEATHER ROOF CEMENT

PURPOSE

Lucas #775 All-Weather Roof Cement - Wet Surface is an asphalt based roof cement designed for repairing roofs and roof flashings that are wet or under water. This permits repairs immediately and can prevent more extensive water damage.

PRODUCT DESCRIPTION

Lucas #775 All-Weather Roof Cement is manufactured from Type I Roofing Asphalt, non-asbestos reinforcing fibers, petroleum solvents and a special additive which displaces moisture and allows application to wet surfaces

APPLICATION

The surface to be repaired must be clean and free of debris. Apply #775 evenly with a pointed roofer's trowel or gloved hand. Use sufficient pressure to force water out from underneath the mastic as it is applied. #775 should be applied 1/8 to 1/4 of an inch thick and may be reinforced with glass membrane or polyester fabric to strengthen the repair. Repairs made to wet surfaces should be considered temporary as trapped moisture will expand when heated by the sun causing blisters and potentially new leaks. When making a permanent repair, open up the area and allow it to dry thoroughly. Clean up with mineral spirits and waterless hand cleaner.

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

#775 SPECIFICATION

Applicable Specification	ASTM D 4586 Type I Class II
Recommended Rate of Application	1/8 to 1/4 inch thick
% Asphalt	55 min
% Solids	73 min
% Non-volatile	82 max
Weight per gallon	8.5 lbs.
Flash Point (TCC)	+100°F (38.7°C)
Container Sizes	5, 3 and 1 gallon

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.