

LUCAS *Coatings & Mastics for the Roofing Trade*

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

PRODUCT DATA BULLETIN

#310 KWIK-DRY PRIMER

PURPOSE

Lucas #310 Kwik-Dry Primer is a extremely fast drying asphalt primer intended for use on concrete, masonry, wood decks and parapet walls prior to application of asphalt built up or modified bitumen roofing systems. It should also be used before resurfacing weathered asphalt and granular surfaced modified bitumen roofs. Kwik-Dry Primer's improved drying time allows traffic on the primed surfaces sooner and faster application of the roof system.

PRODUCT DESCRIPTION

Kwik-Dry Primer is manufactured from refined high softening-point asphalt, high-flash Naphtha, and a special penetrating additive. In addition to penetrating and securely bonding to these difficult to adhere to surfaces, Lucas #310 dries much faster than conventional asphalt primers which are cutback with Mineral Spirits.

APPLICATION

Apply #310 by brush, roller or spray at a rate of 1/2 gallon per 100 sq. ft. More may be necessary on more porous surfaces, however increased rates of application will extend the drying time. Do not allow foot traffic until completely dry.

CAUTION

Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Do not use near heat or open flame. Keep out of reach of children. Read MSDS prior to use.

#310 SPECIFICATION

Applicable Specification	ASTM D 41
Viscosity ASTM D-562	75g @ 77°F (25°C) 150 cps
Recommended rate of application	1/2 gal. per 100 sq. ft.
% Asphalt	50 min
% Solids	45 min
% Non-volatile	50 max
Weight per gallon	7.1 lbs.
Flash Point (TCC)	+100°F (38.7°C)
Container Sizes	1, 5, 55, Aerosol Spray

Information contained in this bulletin is offered gratis on the basis of our field experience and laboratory tests conducted carefully by using modern equipment verified for accuracy. No warranty is expressed or implied beyond the purchase price of the material. We suggest that the user evaluate the product's suitability for a particular use prior to application. We reserve the right to improve, change, or discontinue specifications and products without prior notice.