



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#201 FIBRATED FOUNDATION COATING STANDARD

#201 SPECIFICATION

ASTM D 4479
IRC 406.1, IBC 1801.2

Viscosity	ASTM D 2196	80,000 cps
Solids by Weight	ASTM D 1644	74%
Solids by Volume	ASTM D 2697	72%
% Asphalt	ASTM D 6511	67%
Weight Per Gallon	ASTM D 1147	8.2 lbs.
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<270 g/l

PRODUCT DESCRIPTION

Lucas #201 Fibrated Foundation Coating is a fast drying fiber reinforced asphalt coating intended for application to below-grade foundation walls. Fibrated coatings allow greater film thickness than non-fibrated coatings or hot mopped asphalt.

Lucas #201 is manufactured from high softening point asphalts, petroleum solvents and reinforcing fibers. It is filtered for spray upon request.

APPLICATION

The surface to be coated must be clean and dry. Apply #201 at a rate of 3 gallons per 100 square feet with a brush, roller or suitable spray equipment. Additional coats may be applied to achieve the desired film thickness. If desired, seal form ties with Lucas #279 prior to coating the foundation with #201.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

Container Sizes: 5, 55 gallon

Colors: Black

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.