



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#5600 GUTTER SEAL



PRODUCT DESCRIPTION

#5600 Gutter Seal is a multipurpose, nitrile elastomer based self-leveling sealant specifically designed as a narrow seam sealant for gutter lap joints on new gutter installations. Low modulus and high elongation accommodate severe movement. Excellent adhesion to metal gutters. For a non-sag, clear sealant, or for a gutter repair sealant, please refer to Lucas #6700 Terpolymer Gutter Seal. Recommended for properly draining gutters. Not recommended for immersion.

APPLICATION

Surface to be sealed must be clean. To use, cut tip to size and puncture seal. Maximum recommended joint width is 1/8 inch. Apply two 1/8 inch beads to the edge of the gutter lap and slide the two pieces together to ensure full contact. Apply a second 1/8 inch bead to the lap seam on the interior of the gutter. Please read the most current SDS for this product prior to use. #5600 may be painted. Some paints may require up to one week cure time before application. For outdoor use only. Keep product warm prior to use.

Clean up: Clean up with MEK or Acetone

Shelf Life: One year from the date of manufacture.

WARNING! FLAMMABLE MIXTURE, Contains t-butyl acetate and petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

#5600 SPECIFICATION

Viscosity	ASTM D 2196	350,000 cps
Solids by Weight	ASTM D 1644	42%
Solids by Volume	ASTM D 2697	40%
Weight Per Gallon	ASTM D 1147	7.5 lbs.
Tensile Strength	ASTM D 2370	300 psi
Elongation	ASTM D 2370	1200%
Movement	ASTM C 719	+/-25%
Skin Time	ASTM C 679	15 Minutes
Tack Free	ASTM C 679	20 Minutes
Flash Point	ASTM D 56	62°F / 17°C
VOC	EPA 24	< 4%

Container Sizes: 10 oz. fiber cartridge, 5 oz. aluminum squeeze tube

Colors: Aluminum

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.