



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#5900 CLEAR BRUSHABLE SEALANT SOLVENT-BASED

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

#5900 SPECIFICATION

ASTM D-6083

PRODUCT DESCRIPTION

Polymer based Lucas #5900 Clear Brushable Sealant is an elastomeric solvent based coating intended for waterproofing fiberglass roof panels and translucent skylights. #5900 is also an ideal sealant for metal gutters and other decorative metal surfaces.

PRODUCT DESCRIPTION

Lucas #5900 is based on tough Styrene Ethylene/Butylene Styrene polymers and a clear adhesive hydrocarbon resin in an aromatic hydrocarbon vehicle. High loadings of anti-oxidants and light stabilizers ensure durability throughout roof service life.

APPLICATION

Surface to be coated must be dry and free of dirt or corrosion particles. Mechanically mix product before using. Avoid entraining air in the product. All seams, fasteners and penetrations should be sealed with #5500 Seam Sealer or #6600 Universal™ Sealant – Clear. Apply in two coats of 1 gallon per one hundred square feet each. For best results, apply coating in one direction with the slope of the roof. Roofing asphalts may cause staining. As this condition is unpredictable, we recommend that the user apply a small amount of #5900 to the area of the roof to be coated in order to test its performance. Use #5900 as it comes from the container, no thinning is necessary with this product.

The preceding directions are basic guidelines only. Please read and understand the complete Lucas Guide Specification for this product for the intended application. The Guide Specification is available from techsupport@rmlucas.com

Clean up: Clean up with Lucas #125 Safe Solve™.

Shelf Life: Two years from the date of manufacture.

*Roof surfaces must be dry for coating application. Even when the surface appears dry, moisture trapped in the roof, deck or insulation. A moisture scan is recommended prior to application. Application of this coating within 5°F of the dew point is not recommended. For more information on dew point calculation, see FAQs at rmlucas.com.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

Viscosity	ASTM D 2196	1,200 cps
Solids by Weight	ASTM D 1644	39%
Solids by Volume	ASTM D 2697	37%
Weight Per Gallon	ASTM D 1147	7.5 lbs.
Tensile Strength	ASTM D 2370	1800 psi
Elongation	ASTM D 2370	1000%
Reflectivity – Initial	ASTM C 1549	NA
Reflectivity – Aged	ASTM D 1918	NA
Emissivity	ASTM C 1371	NA
SRI	LEED	NA
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	< 550 g/l

Container Sizes: 5, 55 gallon

Colors: Clear

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

1-2015

BODY BUILT BY
B. HEINIG
1464-1466 WEBSTER AV.