



# LUCAS Professional Coatings, Sealants & Adhesives

R. M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

## SAFETY DATA SHEET

Phone: (773)-523-4300

Date of preparation: 1-2-2014

Product(s): Lucas #010, #071

Prepared by: R. Barry

For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

### SECTION I PRODUCT IDENTIFICATION

CHEMICAL FAMILY: Coal Tar

FORMULA: Mixture

#### HAZARDOUS INGREDIENTS:

| <u>NAME</u>               | <u>C.A.S. #</u> | <u>EXPOSURE LIMITS</u>  | <u>% by Weight</u> |
|---------------------------|-----------------|---|--------------------|
| Coal Tar Pitch *          | 8001-58-9       | OSHA TWA: .2 mg/m <sup>3</sup>                                    | 70-90              |
| High Flash Naphtha        | 64742-95-6      | OSHA PEL: 100ppm<br>ACGIH: 100ppm                                 | 0-10               |
| ~*1,2,4, Trimethylbenzene | 95-63-6         | OSHA TWA: 25ppm<br>ACGIH TWA: 25ppm                               | 0-4                |
| ~*Xylene                  | 1330-20-7       | OSHA TWA: 100ppm<br>ACGIH TWA: 100 ppm                            | 0-.5               |
| ~*Cumene                  | 98-82-8         | OSHA TWA; 50ppm (skin)<br>ACGIH TWA: 50 ppm (skin)                | 0-.5               |
| Allapulgitte clay         | 8031-18-        | OSHA PEL: None<br>ACGIH TLV: 5 MG/M <sup>3</sup>                  | 3-7                |
| Cellulose                 | 9004-34-6       | OSHA PEL: 5 mg/m <sup>3</sup><br>ACGIH TLV: 5 mg/m <sup>3</sup>   | 1-5                |
| Calcium Carbonate         | 1317-65-3       | OSHA PEL: 15 mg/m <sup>3</sup><br>ACGIH TLV: 10 mg/m <sup>3</sup> | 1-5                |
| Amine Salt                | 28701-67-9      | NE  | <2                 |

~Denotes constituent of above listed ingredient. % Concentration is of product mass.

- Identified as SARA section 313 reportable.

### SECTION II HEALTH / SAFETY ALERT

Pre-existing eye, skin, and respiratory disorders may be aggravated by exposure to these products. Exposure to high concentrations of fumes may have an anesthetic effect. CHRONIC OVER EXPOSURE (as defined by OSHA standards) CAN CAUSE CANCER. Prolonged exposure to vapors can cause severe sunburn. Do not wear contact lenses when using this product.

## **SECTION III PHYSICAL DATA**

**BOILING POINT:** >302° F

**FLASH POINT (SETA):** >105° F

**EVAPORATION RATE:** >1

(butyl acetate = 1.0)

**APPEARANCE AND ODOR:** Black or dark brown liquid or paste of a heavy consistency with an aromatic hydrocarbon odor.

**SPECIFIC GRAVITY:** 1.25

**VAPOR DENSITY:** >1

**SOLUBILITY:** NEG

## **SECTION IV REACTIVITY**

**STABILITY:** Stable

**HAZARDOUS POLYMERIZATION:** Will not occur

**INCOMPATIBILITY:** Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon, various hydrocarbon fragments

## **SECTION V HEALTH HAZARD INFORMATION**

**EYE CONTACT:** Over exposure to fumes can result in irritation and/or corneal changes. These products are irritating to the eyes.

**SKIN CONTACT:** Prolonged exposure to vapors can cause severe sunburn, particularly in sensitive individuals. Contact can cause irritation. When material is not removed immediately or is activated by sunlight a phototoxic skin reaction may result. Repeated and/or prolonged contact can cause more serious skin disorders, including cancer.

**INHALATION:** Overexposure to fumes may result in respiratory tract irritation.

Repeated and/or prolonged exposure to high concentrations of fumes may result in respiratory difficulties, central nervous system effects, and possible cardiovascular problems.

**INGESTION:** Acute gastrointestinal tract irritation, nausea, vomiting, abdominal pain, rapid pulse, and in extreme cases cardiovascular collapse. Fatal dose is approximately 0.1 gram/kilogram of body weight.

## **SECTION VI EMERGENCY / FIRST AID**

**EYE CONTACT:** Flush with water immediately for at least 15 minutes. Seek Medical attention immediately.

**SKIN CONTACT:** Wash skin with waterless hand cleaner followed by soap and water. If redness appears treat it as a sunburn or other chemical burn, if redness persists or rash appears seek medical attention immediately.

**INHALATION:** Remove individual to fresh air, upwind from fume source. If irritation persists seek medical attention immediately.

**INGESTION:** DO NOT INDUCE VOMITING. Prevent aspiration into lungs. Aspiration of even small amounts into lungs may result in aspiration pneumonitis. Give patient large doses of water. Do not give anything by mouth to an unconscious person. Seek medical attention immediately.

## **SECTION VII FIRE & EXPLOSION DATA**

**EXTINGUISHING MEDIA:** Class “B” dry chemical, carbon dioxide, or other suitable extinguishing material such as dry sand. When flames have been eliminated, cover residue with dry extinguishing agent or dry sand and allow it to sit quietly until it has cooled. If fire appears to increase in intensity, stop using these agents. Apply Class “D” extinguishing agent or more dry, inert, granular material. Ring fire with extinguishing material and allow the fire to burn out.

**SPECIAL FIRE FIGHTING PROCEDURES:** If the fire does not respond to above agents or they are not available, use foam or water FOG as a last resort. Water may also be used to cool exposed, but not burning, containers. Personnel fighting fire should use a self-contained breathing apparatus.

**UNUSUAL FIRE and/or EXPLOSION HAZARDS:** Closed containers may explode in a fire. Keep containers cool and remove to a safe location.

**HAZARD CLASS:** H.M.I.S.; Health = 2, Flammability = 2, Reactivity = 0, PPE = B

## **SECTION VIII HANDLING PRECAUTIONS**

**PRECAUTIONS IN CASE OF SPILL:** Contain spill as quickly as possible. Avoid breathing fumes. Keep flowing material away from heat, sparks, or open flames. Do not smoke near a spill. Use clay (Oil Dry™), sand, earth, etc. to absorb the spill. Put material into a suitable steel drum, which can be closed securely.

**WASTE DISPOSAL:** Bury in an approved landfill according to federal, state, and local regulations. Empty containers that have been completely emptied and the residue allowed to dry are not considered hazardous waste.

**HANDLING & STORAGE PRECAUTIONS:** Store away from heat, sparks, and open flames. Solvent vapors are heavier than air and may be moved from the source location by ventilation systems to points far away. Do not store near oxidizers.

**OTHER PRECAUTIONS:** Keep container closed when not in use. Store in a dry ventilated area. Maintain package labeling during storage.

## **SECTION IX PRECAUTIONS FOR SAFE USE**

**VENTILATION:** For outdoor use only.

**RESPIRATORY PROTECTION:** Use NIOSH approved unit for organic vapor and dusts if product is applied by spray or as required if airborne concentrations are above the TLV.

**PROTECTIVE CLOTHING:** As necessary to prevent wetting of the skin. Certain sun blocking creams may aid in protecting skin against the combined affect of sunlight and coal tar exposure.

**EYE PROTECTION:** As necessary in accordance with 29 CFR 1910.113

**OTHER PRECAUTIONS:** With good industrial hygiene no other precautions should be necessary. These products are intended for professional use only. Use only after the appropriate Lucas Product Data Bulletin has been read and understood.

## **SECTION X COMMENTS**

**DOT INFORMATION:** 5 and 55 gallon containers are not regulated

The information contained herein is based on the best available data at the date hereof. No warranty of merchantability, fitness for any use, or any other warrant is expressed or implied regarding the accuracy of this data, the results to be obtained from the use of these products, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall

**make his/her own determination as to the suitability of the product for a particular purpose and on the condition that he/she assumes the risk of his/her use thereof.**