## #2100 BLOCK FILLER

## PRODUCT DESCRIPTION

Lucas #2100 Block Filler is a water-based acrylic coating designed to fill pits and capillaries in concrete block walls prior to coating with Lucas #2000 Elastomeric Wall Coating.

#2100 is manufactured from a blend of acrylic binder and mineral filler that produces a strong and impermeable aggregate that will fill holes and prevent air pockets from producing openings in the coating film.

## **APPLICATION**

Mechanically mix before using. Do not store above 90°F. Apply only at temperatures above 40°F and rising with less than 90% humidity and no threat of rain for 48 hours.

Apply with a roller or suitable spray equipment at the rate of 1-2 gallons per 100 sq. ft. per coat. For spray applications back rolling is required. Drying time to top coat @ 70°F is 2 to 4 hours

Clean up: Soap and water (wet coating).

Shelf Life: One year from the date of manufacture

CAUTION: Avoid prolonged contact with or inhalation of fumes. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

## #2100 SPECIFICATION

Viscosity	ASTM D 2196	90,000 cps
Solids by Weight	ASTM D 1644	71%
Solids by Volume	ASTM D 2697	51%
Weight per Gallon	ASTM D 1475	11.7 lbs.
Tensile Strength	ASTM D 2370	200 psi
Elongation	ASTM D 2370	50%
Flash Point	ASTM D56	NA
VOC	EPA 24	13 g/l

Container Sizes: 1, 5 gallon

Colors: Gray

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER **MAKES** NO WARRANTY MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND **EXPRESS** OR **IMPLIED BEYOND** TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by and/or incorrect misuse application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective Seller's material. at option. Under circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.