



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#7016 PAVER RE-SEALER SOLVENT – BASED SATIN FINISH

#7016 SPECIFICATION

ASTM C-1315*, Type I, Class C
ASTM C-309, Type I, Class A & B
AASHTO M-148, Type 1, Class A
* does not meet flash point requirement

PRODUCT DESCRIPTION

Lucas #7016 Paver Re-Sealer Solvent-Based is a VOC compliant solvent borne acrylic protective coating for resealing previously sealed concrete pavers. #7016 will penetrate the surface and bind the concrete together minimizing erosion of the surface while improving the color and appearance of the surface. As the product seals the paver surface, it will also penetrate and bind together the sand in the paver joints. This limits movement, retards the growth of weeds and inhibits insects such as ants that displace the joint sand.

APPLICATION

Do not apply to concrete pavers in temperatures over 80° F to avoid blistering or pin-holing. Not resistant to petroleum products or animal fats. 24 hours after application.

Apply product as it comes from the container with a high volume commercial pump sprayer with a 1/2 gallon per minute tip or with a 3/4 inch nap roller. Do not use form oil sprayers as the oil will contaminate the sealer. Apply 150 ft. per gallon.

Clean up: Lucas #125 Safe Solve™.

Shelf Life: Two years from the date of manufacture.

WARNING! FLAMMABLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges ^{PH015} is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.



California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

Viscosity	ASTM D 2196	150 cps
Solids by Weight	ASTM D 1644	16%
Solids by Volume	ASTM D 2697	10%
Weight per Gallon	ASTM D 1475	7.3 lbs.
Flash Point	ASTM D56	-4 F (-20° C)
VOC (7016 Standard)	EPA 24	< 350 g/l
VOC (7016CARB)	EPA 24	< 100 g/l
VOC (7016V)	EPA 24	< 700 g/l

7016CARB is California VOC compliant.
7016V is available for areas regulated under the National VOC rule.

Container Sizes: 1, 5, 55 gallon

Colors: Clear

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.