



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: GB/T 17519-2013

Issue Date 29-May-2015

Revision Date 02-Jun-2015

Version 1

Product identifier

Product Name Alkyd Primer

Other means of identification

Product Code LUCAS 1025

UN/ID no. UN 1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Primers.

Uses advised against For exterior use only. Do not use indoors. Use with adequate ventilation. Keep airborne concentrations below legal and recommended limits.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company
3211 South Wood Street
Chicago, Illinois 60608
(773) 523-4300

Emergency telephone number

Emergency Telephone For Hazardous Materials [or Dangerous Goods] Incident , Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 USA and Canada: +1 703-527-3887

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation
May cause genetic defects
May cause cancer
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Appearance Gray Liquid

Physical state Liquid

Odor Aromatic

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed when product is not in use.
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see first aid information on this label)
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- May be harmful if swallowed
- May be harmful in contact with skin
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life

Unknown acute toxicity 38% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
VM & P Naphtha	8032-32-4	20 - 30%	*
Zinc	7440-66-6	10 - 20%	*
Xylene, mixed isomers, pure	1330-20-7	10 - 20%	*
Silica, quartz	14808-60-7	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store in a dry place away from excessive heat, in original or similar waterproof containers. Keep away from heat, sparks, flame and other sources of ignition.

Incompatible materials Acids. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
VM & P Naphtha 8032-32-4	-	(vacated) TWA: 300 ppm (vacated) TWA: 1350 mg/m ³ (vacated) STEL: 400 ppm (vacated) STEL: 1800 mg/m ³	Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Xylene, mixed isomers, pure 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Silica, quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	(vacated) TWA: 0.1 mg/m ³ respirable dust : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Aromatic
Appearance	Gray Liquid	Odor threshold	No information available
Color	Grey		
Property	Values	Remarks • Method	
pH	No information available		
Melting point/freezing point	No information available		
Boiling point / boiling range	122 °C		
Flash point	> 13 °C / > 56 °F	Tag Closed Cup	
Evaporation rate	Slower than Ether		
Flammability (solid, gas)	No information available		

Flammability Limit in Air		For exterior use only. Do not use indoors.
Upper flammability limit:	7%	
Lower flammability limit:	.9%	
Vapor pressure	5.2	@ 20 °C
Vapor density	Heavier than Air	
Specific Gravity	1.4	
Water solubility	Immiscible in water	
Solubility in other solvents	No information available	Soluble in aromatic and aliphatic solvents.
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	Less than 375 g/l.
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Acids. Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available.
Inhalation	Inhalation of process vapors may cause respiratory irritation. Toxic by inhalation.
Eye contact	Avoid contact with eyes.
Skin contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
VM & P Naphtha 8032-32-4	-	-	= 3400 ppm (Rat) 4 h
Xylene, mixed isomers, pure 1330-20-7	= 4300 mg/kg (Rat)	-	= 47635 mg/L (Rat) 4 h
Silica, quartz 14808-60-7	= 500 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene, mixed isomers, pure 1330-20-7	-	Group 3	-	-
Silica, quartz 14808-60-7	A2	Group 1	Known	X

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 3,220.00

ATEmix (dermal) 4,871.00

ATEmix (inhalation-dust/mist) 6.64

12. ECOLOGICAL INFORMATION**Ecotoxicity**

46 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
VM & P Naphtha 8032-32-4	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
Zinc 7440-66-6	0.11 - 0.271: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.09 - 0.125: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	2.16 - 3.05: 96 h Pimephales promelas mg/L LC50 flow-through 0.211 - 0.269: 96 h Pimephales promelas mg/L LC50 semi-static 2.66: 96 h Pimephales promelas mg/L LC50 static 30: 96 h Cyprinus carpio mg/L LC50 0.45: 96 h Cyprinus carpio mg/L LC50 semi-static 7.8: 96 h Cyprinus carpio mg/L LC50 static 3.5: 96 h Lepomis macrochirus mg/L LC50 static 0.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.59: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.41: 96 h Oncorhynchus mykiss mg/L LC50 static	0.139 - 0.908: 48 h Daphnia magna mg/L EC50 Static
Xylene, mixed isomers, pure 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

		static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	
--	--	---	--

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene, mixed isomers, pure 1330-20-7	3.15

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging

Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers, pure 1330-20-7	-	Included in waste stream: F039	-	U239

Chemical Name	California Hazardous Waste Status
Zinc 7440-66-6	Ignitable powder Toxic
Xylene, mixed isomers, pure 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT Regulated
UN/ID no. UN 1263
Proper shipping name Paint
Hazard Class 3
Packing Group II
Special Provisions Not regulated for ground transport when shipped 1000 lbs or less.

TDG Not regulated.**MEX** Not regulated.**ICAO (air)** Not regulated.**IATA** Not regulated.**IMDG** Not regulated.**RID** Not regulated.**ADR** Not regulated.**ADN** Not regulated.

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Zinc - 7440-66-6	1.0
Xylene, mixed isomers, pure - 1330-20-7	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	Yes

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6	-	X	X	-
Xylene, mixed isomers, pure 1330-20-7	100 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Zinc 7440-66-6	1000 lb	-	RQ 454 kg final RQ RQ 1000 lb final RQ
Xylene, mixed isomers, pure 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Silica, quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
VM & P Naphtha 8032-32-4	X	-	X
Zinc 7440-66-6	X	X	X

Xylene, mixed isomers, pure 1330-20-7	X	X	X
Silica, quartz 14808-60-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 1	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 3	Physical hazards 1	Personal protection X

Prepared By Prepared by Robert Barry
 Issue Date 29-May-2015
 Revision Date 02-Jun-2015

Revision Note
 No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet