

# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 11-May-2015 Revision Date 21-May-2015 Version 1

Product identifier

Product Name Terpolymer Gutter Seal - Clear

Other means of identification

Product Code LUCAS 6700 CLEAR

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant.

**Uses advised against** For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company

3211 South Wood Street Chicago, Illnois 60608 (773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300 Outside USA and Canada: 1-703-527-3887

# 2. HAZARDS IDENTIFICATION

# Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

#### Label elements

# **Emergency Overview**

#### Danger

#### Hazard statements

Harmful if inhaled Causes skin irritation

Causes serious eye irritation

May be fatal if swallowed and enters airways

Flammable liquid and vapor



\_\_\_\_\_

 Appearance Viscous
 Physical state Paste/Gel
 Odor Solvent (Mineral Spirits) Aromatic

#### **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Keep away from heat/sparks/open flames/hot surfaces.

Keep container tightly closed when product is not in use.

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

Specific treatment (see first aid information on this label)

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown acute toxicity 61% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

# **Substance**

#### **Mixture**

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name Sealant and Caulk.

Synonyms None.

Chemical nature Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Hydrocarbon Resin	69430-35-9	30 - 40%	*
Styrene/Butadiene Copolymer	66070-58-4	20 - 30%	*
Aromatic Naptha (with <0.1% Benzene)	64742-95-6	20 - 30%	*
1,2,4 Trimethylbenzene	95-63-6	10 - 20%	*
Amorphous Silica (Silicon Dioxide)	7631-86-9	0 - 10%	*

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the

brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling

contents may be harmful or fatal.

Eye contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin contact** Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a

physician.

**Inhalation** Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with

breathing is experienced, get medical attention immediately.

Ingestion Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical

attention immediately.

**Self-protection of the first aider** First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

**Symptoms** May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

**Explosion data** 

Sensitivity to Mechanical Impact Not sensitive.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

# Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use

personal protective equipment as required.

\_\_\_\_\_

Other Information Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

**Environmental precautions** 

**Environmental precautions** Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous

earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled

containers for disposal according to local / national regulations (see Section 13).

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition.

Incompatible materials Strong acids. Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

**Exposure Guidelines** No ACGIH or OSHA PEL is assigned to this mixture.

Exposure limits for the component materials are shown below.

This product, as supplied, is not believed to contain any hazardous material that exceeds

exposure limits established by OSHA.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4 Trimethylbenzene	-	-	TWA: 25 ppm
95-63-6			TWA: 125 mg/m <sup>3</sup>
Amorphous Silica (Silicon Dioxide)	-	(vacated) TWA: 6 mg/m <sup>3</sup> <1%	IDLH: 3000 mg/m <sup>3</sup>
7631-86-9		Crystalline silica	TWA: 6 mg/m <sup>3</sup>
		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m³ TWA	

**Appropriate engineering controls** 

Engineering Controls Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical

cross ventilation. Ventilation pattern should be designed to prevent accumulation of asphalt vapors. Ventilation must be sufficient to maintain asphalt vapor concentrations below the

TWA limits outlined above.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing that is resistant to chemical penetration.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection

should be worn.

Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated **General Hygiene Considerations** 

clothing before reuse.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste/Gel

Viscous Odor Solvent (Mineral Spirits) **Appearance** 

Aromatic

Clear Various Odor threshold 1-30 PPM. Odor Color

thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.

**Property** Values Remarks • Method

Not applicable Hq

None / -70 °C None / -94 °F Melting point/freezing point

Boiling point / boiling range > 154 °C / 310 °F

Flash point

**Evaporation rate** 0.1

Flammability (solid, gas)

Flammability Limit in Air

> 40.5 °C / > 105 °F Setaflash

Butly acetate = 1 No information available

Flammable above 105 degrees F and 40.5 degrees

Melting Point is not applicable. Freezing points are

@ 20 °C

Water = 1g/ml

No data available.

shown.

Upper flammability limit: 7.0 Lower flammability limit: 1.6

Vapor pressure 0.3 (kPa)

Vapor density 5.3 Where: Air = 1 at 68 degrees F (20 degrees C)

**Specific Gravity** 1-1.1 Water solubility Insoluble

Solubility in other solvents Soluble in aromatic and aliphatic

solvents.

**Partition coefficient** No information available

**Autoignition temperature Decomposition temperature** 

Kinematic viscosity Dynamic viscosity

No information available **Explosive properties** 

Vapor accumulation could flash or explode if ignited.

330 °C / 626 °F

No information available

No information available

**Oxidizing properties** None

Other Information

Not applicable Softening point

Molecular weight No information available Less than 300 g/l **VOC Content (%)** 8.3 to 8.5 lb/gal Density Not applicable **Bulk density** 

#### 10. STABILITY AND REACTIVITY

Reactivity

Not applicable Not applicable

#### **Chemical stability**

Stable.

#### **Possibility of Hazardous Reactions**

None under normal use.

**Hazardous polymerization** Hazardous polymerization does not occur.

#### **Conditions to avoid**

Avoid static discharge. Avoid heat, sparks, and open flame.

Incompatible materials

Strong acids. Strong oxidizing agents. **Hazardous Decomposition Products** 

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information Toxicological testing has not been conducted for this product overall. Available toxicological

data for individualing redients are summarized below.

**Inhalation** Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes. Contact with eyes may cause irritation.

**Skin contact** May cause irritation.

Ingestion If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected

route of exposure.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	= 8400 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	= 3400 ppm (Rat) 4 h
1,2,4 Trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg ( Rabbit )	= 18 g/m³ ( Rat ) 4 h
Amorphous Silica (Silicon Dioxide) 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L (Rat ) 1 h

#### Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Can cause skin irritation.

Serious eye damage/eye irritation Irritating to eyes.

**Irritation** Irritating to eyes, respiratory system and skin.

Corrosivity Not classified.

**Sensitization** May cause sensitization of susceptible persons.

**Germ cell mutagenicity**This product does not contain any ingredients that cause germ cell mutagenicity.

Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed

any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Amorphous Silica (Silicon	-	Group 3	-	-
Dioxide)				
7631-86-9				

#### Legend

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen. Reproductive toxicity None known.

\_\_\_\_\_

**Developmental Toxicity Teratogenicity**None known.
None known.

STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.

#### Numerical measures of toxicity - No information available

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

 ATEmix (oral)
 5,268.00

 ATEmix (dermal)
 2,281.00

 ATEmix (inhalation-dust/mist)
 4.50

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The following table lists information related to aquatic toxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Amorphous Silica (Silicon Dioxide) 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
1,2,4 Trimethylbenzene 95-63-6	3.63

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable local, regional, national and international

laws and regulations.

**Contaminated packaging** Do not reuse container.

#### 14. TRANSPORT INFORMATION

**DOT** Regulated DOT Ground: Not regulated if shipped in containers < 119 gallons (450 liters).

Combustible liquid, n.o.s (mineral spirits)

DOT Ground: Regulated if shipped in containers >119 gallons (450 liters).

Proper shipping name

Hazard Class 3
Packing Group III

TDG Regulated UN/ID no. NA 1993

**Proper shipping name**Combustible liquid, n.o.s (mineral spirits)

Hazard Class 3
Packing Group III

MEX Regulated NA 1993

**Proper shipping name**Combustible liquid, n.o.s. (mineral spirits)

ICAO (air)RegulatedUN/ID no.1993

LATA Regulated UN/ID no. 1993

IMDG Regulated UN/ID no. 1993

RID Not applicable in the United States.

ADR Not applicable in the United States.

ADN Not applicable in the United States.

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

**DSL/NDSL** All of the components of this product are listed on the DSL.

<u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

# CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive

\_\_\_\_\_

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

# **US State Regulations**

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

This product contains the following substances regulated by various State Right-to-Know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,2,4 Trimethylbenzene 95-63-6	Х	X	X
Amorphous Silica (Silicon Dioxide) 7631-86-9	Х	X	X

#### **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and Chemical

Properties HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection -

Chronic Hazard Star Legend \*= Chronic Health Hazard

Issue Date 11-May-2015 Revision Date 21-May-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**