



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: GB/T 17519-2013

Issue Date 29-May-2015

Revision Date 04-Jun-2015

Version 1

Product identifier

Product Name Cure & Seal

Other means of identification

Product Code LUCAS 7000V

UN/ID no. 1268

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent.

Uses advised against For exterior use only. Do not use indoors. Use with adequate ventilation. Keep airborne concentrations below legal and recommended limits.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company
3211 South Wood Street
Chicago, Illinois 60608
(773) 523-4300

Emergency telephone number

Emergency Telephone For Hazardous Materials [or Dangerous Goods] Incident , Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300 USA and Canada: +1 703-527-3887

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause cancer

May damage fertility or the unborn child

May cause respiratory irritation

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Store in a dry place away from excessive heat, in original or similar waterproof containers. Keep away from heat, sparks, flame and other sources of ignition.

Incompatible materials Acids. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Diocetylphthalate 117-81-7	TWA: 5 mg/m ³	(vacated) TWA: 5 mg/m ³ Di-sec-octyl phthalate (vacated) STEL: 10 mg/m ³ Di-sec-octyl phthalate	IDLH: 5000 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³ Di-sec octyl phthalate which is not correct for 117-81-7

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Solvent
Appearance	Clear	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks • Method	
pH	No information available		
Melting point/freezing point	No information available		
Boiling point / boiling range	55 °C 132		
Flash point	> -20 °C / > -4 °F	Tag Closed Cup	
Evaporation rate	7.7	Butly acetate = 1	
Flammability (solid, gas)	No information available		
Flammability Limit in Air		For exterior use only. Do not use indoors.	
Upper flammability limit:	2.6%		
Lower flammability limit:	12.8%		
Vapor pressure	185	@ 20 °C	
Vapor density	Heavier than Air		

Specific Gravity	.78	
Water solubility	Immiscible in water	
Solubility in other solvents	No information available	Soluble in aromatic and aliphatic solvents.
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	<700 g/l
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Acids. Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available.
Inhalation	Inhalation of process vapors may cause respiratory irritation. Toxic by inhalation.
Eye contact	Avoid contact with eyes.
Skin contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 4300 mg/kg (Rat)	-	= 47635 mg/L (Rat) 4 h
Diocetylphthalate 117-81-7	= 6860 mg/kg (Rat)	= 25 g/kg (Rabbit)	> 10.62 mg/L (Rat) 4 h > 23.67 mg/L (Rat) 1 h

Information on toxicological effects**Symptoms** No information available.**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Diethylphthalate 117-81-7	A3	Group 2B	Reasonably Anticipated	X

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 4,389.00
ATEmix (dermal) 1,160.00
ATEmix (inhalation-dust/mist) 1.50

12. ECOLOGICAL INFORMATION

Ecotoxicity

26 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Diethylphthalate 117-81-7	130: 72 h Desmodesmus subspicatus mg/L EC50 0.1: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.1: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	0.16: 96 h Pimephales promelas mg/L LC50 static 0.200: 96 h Lepomis macrochirus mg/L LC50 static 0.200: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.27 - 0.67: 96 h Pimephales promelas mg/L LC50 flow-through 0.32: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.32: 96 h Oryzias latipes mg/L LC50 semi-static 0.32: 96 h Brachydanio rerio mg/L LC50 semi-static 0.32: 96 h Poecilia reticulata mg/L LC50 semi-static 0.67: 96 h Oryzias latipes mg/L LC50 flow-through 100: 96 h Oncorhynchus mykiss mg/L LC50 static	0.16: 48 h Daphnia magna mg/L EC50 9.4: 48 h Daphnia magna mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	3.15
Diethylphthalate 117-81-7	5.03

Other adverse effects No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes** Disposal should be in accordance with applicable local, regional, national and international laws and regulations.**Contaminated packaging** Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Diethylphthalate 117-81-7	U028	Included in waste stream: F039	-	U028

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION**DOT**

UN/ID no. 1268
Proper shipping name Flammable liquids, n.o.s.(Acetone, Petroleum distillates)
Hazard Class 3
Packing Group II
Special Provisions Not regulated for ground transport in containers less than one liter including aerosols.

TDG Not regulated.**MEX** Not regulated.**ICAO (air)** Not regulated.**IATA** Not regulated.**IMDG** Not regulated.**RID** Not regulated.**ADR** Not regulated.**ADN** Not regulated.**15. REGULATORY INFORMATION****International Inventories****Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
Diethylphthalate - 117-81-7	0.1

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	Yes

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Diethylphthalate 117-81-7	-	X	X	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Diethylphthalate 117-81-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Diethylphthalate - 117-81-7	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Diethylphthalate 117-81-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

