



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#316 ASPHALT PRIMER

#316 SPECIFICATION

ASTM D 41

PRODUCT DESCRIPTION

Lucas #316 Asphalt Primer is a fast drying asphalt primer intended for use on concrete, masonry, wood decks and parapet walls prior to application of asphalt built up or modified bitumen roofing systems. It should also be used before resurfacing weathered asphalt and granular surfaced modified bitumen roofs.

#316 Asphalt Primer is manufactured from refined high softening-point asphalt and fast drying petroleum solvents.

APPLICATION

Apply #316 rate of 1/2 gallon per 100 sq. ft. More may be necessary on more porous surfaces; however increased rates of application will extend the drying time. Do not allow foot traffic until completely dry.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

Viscosity	ASTM D 2196	500 cps
Solids by Weight	ASTM D 1644	63%
Solids by Volume	ASTM D 2697	61%
% Asphalt	ASTM D 6511	62%.
Weight Per Gallon	ASTM D 1147	7.8 lbs.
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<350 g/l

Container Sizes: 1, 5, 55 gallon

Colors: Black

This product is Florida Building Code approved.



TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

