



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#402 EPDM NON-SLIP TRAFFIC SURFACING

Container Sizes: 5 (30 lbs)

Standard Colors: Gray and Safety Yellow

Shelf Life: 5 years.

PRODUCT DESCRIPTION

Lucas #402 EPDM Non-Slip Traffic Surfacing for walkways and applications where foot traffic is expected on Lucas #8000 Silicone Roof Coating. Lucas #402 EPDM granules may be embedded in the surface of the coating to provide a more durable and damage and slip-resistant surface.

APPLICATION

Mechanically mix the #8000 coating prior to application. Surface to be coated must be dry and free of dirt or corrosion particles. Gray #8000 coating is recommended for use with gray granules however white will also have a very good appearance. Apply coat of #8000 at a rate of 1 gallon per 100 sq. ft. and immediately apply the granules at the rate of 15 lbs. per 100 square ft. Do not allow the coating to skin over or the granules will not adhere. More may be applied and vacuumed off after the coating cures. Vacuuming is recommended in order to remove all loose granules and avoid accumulation in gutters or drains. Over time the surface may wear and can be easily repaired or completely resurfaced with additional coating and granules.

Lucas #8000 cures through absorption of moisture from both the substrate and the air. Avoid entraining air when mixing. Cure time will be faster in humid conditions and on substrates that hold moisture such as concrete. Open and partially full containers will skin over quickly. If this occurs, remove the skins and continue using the remaining product.

The above application information is a summary for reference only. Please read the appropriate Lucas Guide Specification for the application of this product before quoting or starting any project.

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

