



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

**Issue Date** 01-Feb-2017

**Revision Date** 02-Jun-2015

**Version** 1

**Product identifier**

**Product Name** Ultraclear Terpolymer Sealant

**Other means of identification**

**Product Code** LUCAS 6600UC

**Synonyms** None

**Recommended use of the chemical and restrictions on use**

**Recommended Use** Sealant.

**Uses advised against** For exterior use only. Do not use indoors.

**Details of the supplier of the safety data sheet**

**Manufacturer Address** R.M. Lucas Company  
3211 South Wood Street  
Chicago, Illinois 60608  
(773) 523-4300

**Emergency telephone number**

**Emergency Telephone** Call CHEMTREC Day or Night:  
Within USA and Canada: 1-800 424-9300  
Outside USA and Canada: 1-703-527-3887

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|   |             |
|---|-------------|
| Acute toxicity - Inhalation (Dusts/Mists) | Category 3  |
| Skin corrosion/irritation                 | Category 2  |
| Serious eye damage/eye irritation         | Category 2  |
| Germ cell mutagenicity                    | Category 1B |
| Carcinogenicity                           | Category 1B |
| Aspiration toxicity                       | Category 1  |
| Flammable liquids                         | Category 3  |

**Label elements**

**Emergency Overview**

|  |
|--|
| <b>Danger</b>  |
| <b>Hazard statements</b><br>Toxic if inhaled<br>Causes skin irritation<br>Causes serious eye irritation<br>May cause genetic defects<br>May cause cancer<br>May be fatal if swallowed and enters airways<br>Flammable liquid and vapor |

**Appearance** Viscous**Physical state** Paste/Gel**Odor** Solvent (Mineral Spirits) Aromatic**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see first aid information on this label)  
 Specific treatment (see first aid information on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity

100% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance****Mixture**

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Common name**

Sealant and Caulk.

**Synonyms**

None.

**Chemical nature**

Organic solvents and additives.

| Chemical Name                        | CAS No.    | Weight-% | Trade Secret |
|--------------------------------------|------------|----------|--------------|
| Hydrocarbon Resin                    | 69430-35-9 | 30 - 40% | *            |
| Styrene/Butadiene Copolymer          | 66070-58-4 | 20 - 30% | *            |
| Aromatic Naptha (with <0.1% Benzene) | 64742-95-6 | 20 - 30% | *            |
| 1,2,4 Trimethylbenzene               | 95-63-6    | 10 - 20% | *            |
| Amorphous Silica (Silicon Dioxide)   | 7631-86-9  | 0 - 10%  | *            |
| Xylene                               | 1330-20-7  | 0 - 10%  | *            |
| Cumene                               | 98-82-8    | 0 - 10%  | *            |

#### 4. FIRST AID MEASURES

##### Description of first aid measures

|   |  |
|---|--|
| <b>General advice</b>                     | Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. |
| <b>Eye contact</b>                        | In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  |
| <b>Skin contact</b>                       | Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.  |
| <b>Inhalation</b>                         | Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.  |
| <b>Ingestion</b>                          | Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.  |
| <b>Self-protection of the first aider</b> | First aider: Pay attention to self-protection!.  |

##### Most important symptoms and effects, both acute and delayed

**Symptoms** May cause skin irritation. May cause eye irritation.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Sand. Use foam or water FOG as a last resort.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

**Hazardous combustion products** Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

##### Explosion data

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

|                                 |  |
|---------------------------------|--|
| <b>Personal precautions</b>     | No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required. |
| <b>Other Information</b>        | Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).   |
| <b>For emergency responders</b> | Use personal protection recommended in Section 8.  |

### Environmental precautions

|                                  |  |
|----------------------------------|--|
| <b>Environmental precautions</b> | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information. |
|----------------------------------|--|

### Methods and material for containment and cleaning up

|  |   |
|--|---|
| <b>Methods for containment</b>         | Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.  |
| <b>Methods for cleaning up</b>         | Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13). |
| <b>Prevention of secondary hazards</b> | Clean contaminated objects and areas thoroughly observing environmental regulations.  |

## 7. HANDLING AND STORAGE

### Precautions for safe handling

|                                |   |
|--------------------------------|---|
| <b>Advice on safe handling</b> | Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors. |
|--------------------------------|---|

### Conditions for safe storage, including any incompatibilities

|                               |   |
|-------------------------------|---|
| <b>Storage Conditions</b>     | Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition. |
| <b>Incompatible materials</b> | Strong acids. Strong oxidizing agents.  |

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

|                            |   |
|----------------------------|---|
| <b>Exposure Guidelines</b> | No ACGIH or OSHA PEL is assigned to this mixture.<br>Exposure limits for the component materials are shown below.<br>This product, as supplied, is not believed to contain any hazardous material that exceeds exposure limits established by OSHA. |
|----------------------------|---|

| Chemical Name                                   | ACGIH TLV                     | OSHA PEL   | NIOSH IDLH   |
|---|-------------------------------|--|--|
| 1,2,4 Trimethylbenzene<br>95-63-6               | -                             | -  | TWA: 25 ppm<br>TWA: 125 mg/m <sup>3</sup>                |
| Amorphous Silica (Silicon Dioxide)<br>7631-86-9 | -                             | (vacated) TWA: 6 mg/m <sup>3</sup> <1%<br>Crystalline silica<br>TWA: 20 mppcf<br>: (80)/(%) SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA | IDLH: 3000 mg/m <sup>3</sup><br>TWA: 6 mg/m <sup>3</sup> |
| Xylene<br>1330-20-7                             | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup>                         | -  |

|                   |             |  |  |
|-------------------|-------------|--|--|
|                   |             | (vacated) STEL: 150 ppm<br>(vacated) STEL: 655 mg/m <sup>3</sup>   |  |
| Cumene<br>98-82-8 | TWA: 50 ppm | TWA: 50 ppm<br>TWA: 245 mg/m <sup>3</sup><br>(vacated) TWA: 50 ppm<br>(vacated) TWA: 245 mg/m <sup>3</sup><br>(vacated) S*<br>S* | IDLH: 900 ppm<br>TWA: 50 ppm<br>TWA: 245 mg/m <sup>3</sup> |

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Controls** Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of vapors. Ventilation must be sufficient to maintain vapor concentrations below the TWA limits outlined above.

### Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective gloves and protective clothing that is resistant to chemical penetration.
- Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations** Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                       |               |                       |  |
|-----------------------|---------------|-----------------------|--|
| <b>Physical state</b> | Paste/Gel     | <b>Odor</b>           | Solvent (Mineral Spirits)  |
| <b>Appearance</b>     | Viscous       |                       | Aromatic   |
| <b>Color</b>          | Clear Various | <b>Odor threshold</b> | 1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances. |

| <u>Property</u>                      | <u>Values</u>               | <u>Remarks • Method</u>                                     |
|--------------------------------------|-----------------------------|---|
| <b>pH</b>                            | Not applicable              |   |
| <b>Melting point/freezing point</b>  | None / -70 °C None / -94 °F | Melting Point is not applicable. Freezing points are shown. |
| <b>Boiling point / boiling range</b> | > 154 °C / 310 °F           | 50 g/l at 23C   |
| <b>Flash point</b>                   | > 40.5 °C / > 105 °F        | Setaflash   |
| <b>Evaporation rate</b>              | 0.1                         | Butly acetate = 1   |
| <b>Flammability (solid, gas)</b>     | No information available    |   |
| <b>Flammability Limit in Air</b>     |                             | Flammable above 105 degrees F and 40.5 degrees C.           |
| <b>Upper flammability limit:</b>     | 7.0                         |   |
| <b>Lower flammability limit:</b>     | 1.6                         |   |
| <b>Vapor pressure</b>                | 0.3 (kPa)                   | @ 20 °C   |
| <b>Vapor density</b>                 | 5.3                         | Where: Air = 1 at 68 degrees F (20 degrees C)               |
| <b>Specific Gravity</b>              | 1-1.1                       | Water = 1g/ml   |
| <b>Water solubility</b>              | Insoluble                   |   |



|                   |                      |                          |   |
|-------------------|----------------------|--------------------------|---|
| Cumene<br>98-82-8 | = 1400 mg/kg ( Rat ) | = 12300 µL/kg ( Rabbit ) | > 3577 ppm ( Rat ) 6 h = 39000<br>mg/m <sup>3</sup> ( Rat ) 4 h |
|-------------------|----------------------|--------------------------|---|

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Can cause skin irritation.  
**Serious eye damage/eye irritation** Irritating to eyes.  
**Irritation** Irritating to eyes, respiratory system and skin.  
**Corrosivity** Not classified.  
**Sensitization** May cause sensitization of susceptible persons.  
**Germ cell mutagenicity** This product does not contain any ingredients that cause germ cell mutagenicity.  
**Carcinogenicity** The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

| Chemical Name                                   | ACGIH | IARC     | NTP                    | OSHA |
|---|-------|----------|------------------------|------|
| Amorphous Silica (Silicon Dioxide)<br>7631-86-9 | -     | Group 3  | -                      | -    |
| Xylene<br>1330-20-7                             | -     | Group 3  | -                      | -    |
| Cumene<br>98-82-8                               | -     | Group 2B | Reasonably Anticipated | X    |

**Legend**

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen.

**Reproductive toxicity** None known for product as a whole.  
**Developmental Toxicity** None known for product as a whole.  
**Teratogenicity** None known.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - No information available**

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 5,170.00  
 ATEmix (dermal) 2,281.00  
 ATEmix (inhalation-dust/mist) 0.97

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

61 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical Name                                      | Algae/aquatic plants                                | Fish   | Crustacea   |
|--|---|--|---|
| Aromatic Naptha (with <0.1% Benzene)<br>64742-95-6 | -   | 9.22: 96 h Oncorhynchus mykiss mg/L LC50   | 6.14: 48 h Daphnia magna mg/L EC50  |
| 1,2,4 Trimethylbenzene<br>95-63-6                  | -   | 7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through   | 6.14: 48 h Daphnia magna mg/L EC50  |
| Amorphous Silica (Silicon Dioxide)<br>7631-86-9    | 440: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 5000: 96 h Brachydanio rerio mg/L LC50 static  | 7600: 48 h Ceriodaphnia dubia mg/L EC50                                   |
| Xylene<br>1330-20-7                                | -   | 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 | 3.82: 48 h water flea mg/L EC50<br>0.6: 48 h Gammarus lacustris mg/L LC50 |

|                   |   |  |   |
|-------------------|---|--|---|
|                   |   | static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 19: 96 h Lepomis macrochirus mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static |   |
| Cumene<br>98-82-8 | 2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static  | 0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static |

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

| Chemical Name                     | Partition coefficient |
|-----------------------------------|-----------------------|
| 1,2,4 Trimethylbenzene<br>95-63-6 | 3.63                  |
| Xylene<br>1330-20-7               | 2.77 - 3.15           |
| Cumene<br>98-82-8                 | 3.7                   |

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging**

Do not reuse container.

**US EPA Waste Number**

U055 U239

| Chemical Name       | RCRA | RCRA - Basis for Listing          | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------------|------|-----------------------------------|------------------------|------------------------|
| Xylene<br>1330-20-7 | -    | Included in waste stream:<br>F039 | -                      | U239                   |
| Cumene<br>98-82-8   | -    | -                                 | -                      | U055                   |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name       | California Hazardous Waste Status |
|---------------------|-----------------------------------|
| Xylene<br>1330-20-7 | Toxic<br>Ignitable                |
| Cumene<br>98-82-8   | Toxic<br>Ignitable                |

**14. TRANSPORT INFORMATION****DOT**

DOT Ground: Not regulated if shipped in containers &lt; 119 gallons (450 liters).



**ADR** Not applicable in the United States.

**ADN** Not applicable in the United States.

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

**DSL/NDSL** All of the components of this product are listed on the DSL.

### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name                    | SARA 313 - Threshold Values % |
|----------------------------------|-------------------------------|
| 1,2,4 Trimethylbenzene - 95-63-6 | 1.0                           |
| Xylene - 1330-20-7               | 1.0                           |
| Cumene - 98-82-8                 | 1.0                           |

#### **SARA 311/312 Hazard Categories**

|  |     |
|--|-----|
| <b>Acute health hazard</b>               | Yes |
| <b>Chronic Health Hazard</b>             | Yes |
| <b>Fire hazard</b>                       | Yes |
| <b>Sudden release of pressure hazard</b> | No  |
| <b>Reactive Hazard</b>                   | No  |

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name       | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Xylene<br>1330-20-7 | 100 lb                      | -                      | -                         | X                          |

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

| Chemical Name       | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)                   |
|---------------------|--------------------------|----------------|--|
| Xylene<br>1330-20-7 | 100 lb                   | -              | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |
| Cumene<br>98-82-8   | 5000 lb                  | -              | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |

### US State Regulations

**California Proposition 65**

This product contains the following Proposition 65 chemicals

| Chemical Name    | California Proposition 65 |
|------------------|---------------------------|
| Cumene - 98-82-8 | Carcinogen                |

**U.S. State Right-to-Know Regulations**

This product contains the following substances regulated by various State Right-to-Know regulations.

| Chemical Name                                   | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| 1,2,4 Trimethylbenzene<br>95-63-6               | X          | X             | X            |
| Amorphous Silica (Silicon Dioxide)<br>7631-86-9 | X          | X             | X            |
| Xylene<br>1330-20-7                             | X          | X             | X            |
| Cumene<br>98-82-8                               | X          | X             | X            |

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

|                                   |                                  |                |                    |                                    |
|-----------------------------------|----------------------------------|----------------|--------------------|------------------------------------|
| <b>NFPA</b>                       | Health hazards 2                 | Flammability 2 | Instability 0      | Physical and Chemical Properties * |
| <b>HMIS</b>                       | Health hazards 2                 | Flammability 2 | Physical hazards 0 | Personal protection -              |
| <i>Chronic Hazard Star Legend</i> | <i>* = Chronic Health Hazard</i> |                |                    |                                    |

Prepared By Prepared by Robert Barry  
 Issue Date 01-Feb-2017  
 Revision Date 02-Jun-2015  
 Revision Note  
 No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**