



# LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

## #215 FORM OIL

### #215 SPECIFICATION

#### PRODUCT DESCRIPTION

Lucas #215 Form Oil is intended for application to all types of concrete forms to aid in their removal and to help eliminate surface voids. Also prevents buildup of concrete mix on tools and equipment.

#215 is a blend of non-staining natural oils that react to form a soapy interface between the surface of the form and the concrete.

#### APPLICATION

Apply #215 by brush, roller or spray immediately prior to pouring the concrete. See below for recommended rates of application.

Recommended rate of Application:

Aluminum, High Density Plywood, Plastic, Steel:  
1000-1500 sq. ft. per U.S. gallon

Medium Density Plywood:  
1000 sq. ft. per U.S. gallon

BB Grade Plyform:  
1000 sq. ft. per U.S. gallon

Plywood & dimensional lumber:  
600 sq. ft. per U.S. gallon

Clean up:  
Lucas #125 Safe Solve™.

Shelf Life:  
Two years from the date of manufacture.

**WARNING!** Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

Viscosity	ASTM D 2196	150 cps
Flash Point	ASTM D 56	338°F (170°C)
VOC	EPA 24	135 g/l

Container Sizes: 5, 55 gallon

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

**NOTE:** Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.