



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#125 SAFE SOLVE™ ASPHALT & SEALANT REMOVER

PRODUCT DESCRIPTION

Lucas #125 Safe-Solve™ is an all-purpose, low-odor, natural solvent cleaner. It's intended for removing tar, asphalt and sealants from equipment and building components including vinyl siding, glass windows and factory finished aluminum trim. Safe-Solve™ is also ideally suited for cleaning tools and equipment. Use to remove asphalt and sealants from hand tools, vehicles, caulking guns and other items.

Safe-Solve's™ slow evaporation rate and excellent solvent power make it ideal for cleaning roof surfaces prior to application of butyl and other sealant tapes. #125 will loosen or dissolve surface contamination while activating the roof surface and the sealant tape to improve the adhesive bond. Safe for use on all types of roofing including TPO, PVC, EPDM, Asphalt and modified bitumen. Asphaltic surfaces will be softened by this product but it will not harm the roof or interfere with tape adhesion when properly applied.

With a flash point in excess of +360° F, Safe-Solve™ can be safely used to soak tools overnight prior to cleaning without creating a fire hazard as with mineral spirits or gasoline. Despite its mild odor, Safe-Solve™ has almost twice the solvent power of mineral spirits. Safe for use on hands and skin. Keep out of eyes.

APPLICATION

For general cleaning, remove as much of the material to be treated as possible before applying this product. Test in an inconspicuous area prior to use. Apply to surface, allow sitting for several minutes, then wiping clean. Repeat as necessary. Rinse area with plain water to remove oily residue.

When using #125 to clean and prep roof surfaces for sealant tape application, apply #125 and wipe with a rag and remove dirt. Wipe with a second clean rag to remove as much of the #125 as possible. Rinsing is not necessary.

95% of residual applied cleaner will evaporate or biodegrade within 28 days. This product may alter the appearance of vinyl siding with a chalky or porous surface and may permanently stain siding if not rinsed off. Tools may be soaked overnight to remove heavy residues of asphalt. Acrylic paint and caulk will be

softened allowing for easier removal. Do not apply to painted surfaces.

Clean up: Clean up with water.

Shelf Life: Two years from the date of manufacture.

WARNING! Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

#125 SPECIFICATION

Viscosity	ASTM D 2196	75 cps
Solids by Weight	ASTM D 1644	0%
% Biobased	ASTM D 2697	90%
Flash Point	ASTM D 56	360°F(182°C)
VOC	EPA 24	< 25 g/l

Container Sizes: 16 oz. aerosol spray, 5, 55

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.