



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 12400 S. Laramie Ave. Alsip, IL 60803 (773) 523-4300 rmlucas.com

#7500 PAVER ADHESIVE SOLVENT-BASED

#7500 SPECIFICATION

PRODUCT DESCRIPTION

Lucas #7500 is a special purpose adhesive designed for securing concrete and natural stone pavers and cap stones. Excellent adhesion even to slightly damp surfaces. Fast bond development allows traffic sooner after application. Use to secure step stones and risers, pool edges, wall cap stones and pavers applied over existing concrete or asphalt pavement.

Lucas #7500 is manufactured from high quality adhesive resins and durable elastomers. Fast drying solvents ensure early tensile and adhesive strength.

APPLICATION

Apply 1/4" beads with a caulking gun 2" apart 90% of the length of the stone or paver. When applied with a trowel, use a 1/8" notched trowel. Apply to the surface and immediately embed the paver. More porous or irregular pavers and natural stone may require more adhesive. Heavier rates of application will extend the cure time. Vertical applications will require bracing for 24 to 48 hours.

Clean up: Clean up with Lucas #125 Safe Solve™.

Shelf Life: Two years from the date of manufacture.

WARNING! FLAMMABLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.



Viscosity	ASTM D 2196	450,000 cps
Solids by Weight	ASTM D 1644	58%
Solids by Volume	ASTM D 2697	54%
Weight Per Gallon	ASTM D 1147	8.1 lbs.
Tensile Strength	ASTM D 2370	300 psi
Elongation	ASTM D 2370	600%
Skin Time	ASTM C 679	10 Minutes
Tack Free	ASTM C 679	2 Hours
Flash Point	ASTM D 56	50° F (10° C)
VOC	EPA 24	< 400 g/l

Not for sale in California

Container Sizes: 5 gallon pails, 30 oz. fiber cartridge

Colors: Tan

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.