



## #759 KWIK-SET DAMP TACK

### #759 SPECIFICATION

#### PRODUCT DESCRIPTION

Lucas #759 is a fast-setting asphalt mastic intended for repairing asphalt roofs in all weather conditions. Cold process sealants eliminate the need for hazardous torches and hot asphalt kettles.

Lucas #759 Kwik-Set Damp Tack is manufactured from refined modified asphalts, a special solvent blend, and reinforcing fibers. The special solvents contained in this product help to create an extremely strong and durable bond between the substrate and promote a fast cure. A thick brushable viscosity allows for faster application than trowel on products and easier re-application of gravel when desired. This product contains a unique surface active agent that allows application to wet and underwater surfaces.

#### APPLICATION

The surface must be clean. Apply with a soft bristle brush at the rate of four gallons per 100 sq. ft. on smooth surfaces roofs and 10 gallons per 100 square feet on gravel roofs. Embed polyester fabric for added strength and durability. Replace gravel if desired.

All application rates are approximate and are derived from our laboratory tests and reported field experience. It is left to the judgment of the applicator to assure that sufficient material is applied for adhesion and coverage. Over application may extend drying time.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

**WARNING! FLAMMABLE LIQUID AND VAPOR.** Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.



ASTM D 4479  
 ASTM D 4586 Type I, Class II (Except for slump)

Viscosity	ASTM D 2196	150,000 cps
Solids by Weight	ASTM D 1644	74%
Solids by Volume	ASTM D 2697	72%
% Asphalt	ASTM D 6511	67%
Weight Per Gallon	ASTM D 1147	8.2 lbs.
Wet Adhesion	ASTM D 3409	>80%
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<270 g/l

Seasonal Grades: Winter, Summer. Results above are for Summer Grade.

Container Sizes: 5 gallon

Colors: Black

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.