



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: GB/T 17519-2013

**Issue Date** 29-May-2015

**Revision Date** 27-Dec-2018

**Version** 2

**Product identifier**

**Product Name** Alkyd Primer

**Other means of identification**

**Product Code** LUCAS 1025

**UN/ID no.** UN 1263

**Synonyms** None

**Recommended use of the chemical and restrictions on use**

**Recommended Use** Primers.

**Uses advised against** For exterior use only. Do not use indoors. Use with adequate ventilation. Keep airborne concentrations below legal and recommended limits.

**Details of the supplier of the safety data sheet**

**Manufacturer Address** R.M. Lucas Company  
3211 South Wood Street  
Chicago, Illinois 60608  
(773) 523-4300

**Emergency telephone number**

**Emergency Telephone** Call CHEMTREC Day or Night:  
Within USA and Canada: 1-800 424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Aspiration toxicity	Category 1
Flammable liquids	Category 2

**Label elements**

**Emergency Overview**

<b>Danger</b>
<b>Hazard statements</b> Causes skin irritation May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Highly flammable liquid and vapor

**Appearance** Gray Liquid**Physical state** Liquid**Odor** Aromatic**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed when product is not in use.  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see first aid information on this label)  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Chemical Name	CAS No.	Weight-%	Trade Secret
VM & P Naphtha	8032-32-4	20 - 30%	*
Zinc	7440-66-6	10 - 20%	*
Xylene, mixed isomers, pure	1330-20-7	10 - 20%	*
Silica, quartz	14808-60-7	0 - 10%	*

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin contact</b>	Wash skin with soap and water.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

No information available.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation, especially in confined areas.

**Environmental precautions**

**Environmental precautions** See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

**7. HANDLING AND STORAGE****Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Store in a dry place away from excessive heat, in original or similar waterproof containers. Keep away from heat, sparks, flame and other sources of ignition.

**Incompatible materials** Acids. Bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
VM & P Naphtha 8032-32-4	-	(vacated) TWA: 300 ppm (vacated) TWA: 1350 mg/m <sup>3</sup> (vacated) STEL: 400 ppm (vacated) STEL: 1800 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Xylene, mixed isomers, pure 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Silica, quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

### **Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

### **Individual protection measures, such as personal protective equipment**

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection** No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	Aromatic
<b>Appearance</b>	Gray Liquid	<b>Odor threshold</b>	No information available
<b>Color</b>	Grey		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	No information available		
<b>Melting point/freezing point</b>	No information available		
<b>Boiling point / boiling range</b>	122 °C		
<b>Flash point</b>	> 13 °C / > 56 °F		Tag Closed Cup
<b>Evaporation rate</b>	Slower than Ether		

<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		For exterior use only. Do not use indoors.
<b>Upper flammability limit:</b>	7%	
<b>Lower flammability limit:</b>	.9%	
<b>Vapor pressure</b>	5.2	@ 20 °C
<b>Vapor density</b>	Heavier than Air	
<b>Specific Gravity</b>	1.4	
<b>Water solubility</b>	Immiscible in water	
<b>Solubility in other solvents</b>	No information available	Soluble in aromatic and aliphatic solvents.
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	Less than 375 g/l.
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY****Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Extremes of temperature and direct sunlight.

**Incompatible materials**

Acids. Bases.

**Hazardous Decomposition Products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

<b>Product Information</b>	No data available.
<b>Inhalation</b>	Inhalation of process vapors may cause respiratory irritation. Toxic by inhalation.
<b>Eye contact</b>	Avoid contact with eyes.
<b>Skin contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
VM & P Naphtha	-	-	= 3400 ppm ( Rat ) 4 h

8032-32-4			
Zinc 7440-66-6	= 630 mg/kg ( Rat )	-	-
Xylene, mixed isomers, pure 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene, mixed isomers, pure 1330-20-7	-	Group 3	-	-
Silica, quartz 14808-60-7	A2	Group 1	Known	X

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 3,220.00

ATEmix (dermal) 4,871.00

ATEmix (inhalation-dust/mist) 6.64

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

14.75% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
VM & P Naphtha 8032-32-4	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
Zinc 7440-66-6	0.09 - 0.125: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.11 - 0.271: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	2.16 - 3.05: 96 h Pimephales promelas mg/L LC50 flow-through 2.66: 96 h Pimephales promelas mg/L LC50 static 7.8: 96 h Cyprinus carpio mg/L LC50 static 0.211 - 0.269: 96 h Pimephales promelas mg/L LC50 semi-static 30: 96 h Cyprinus carpio mg/L LC50 3.5: 96 h Lepomis macrochirus mg/L LC50 static 0.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.45: 96 h Cyprinus carpio mg/L LC50 semi-static 0.59: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.41: 96 h Oncorhynchus mykiss mg/L LC50 static	0.139 - 0.908: 48 h Daphnia magna mg/L EC50 Static
Xylene, mixed isomers, pure 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

		Lepomis macrochirus mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static	
--	--	--	--

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Xylene, mixed isomers, pure 1330-20-7	2.77 - 3.15

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging**

Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene, mixed isomers, pure 1330-20-7	-	Included in waste stream: F039	-	U239

Chemical Name	California Hazardous Waste Status
Zinc 7440-66-6	Ignitable powder Toxic
Xylene, mixed isomers, pure 1330-20-7	Toxic Ignitable

**14. TRANSPORT INFORMATION****DOT**

UN/ID no.	Regulated
Proper shipping name	UN 1263
Hazard Class	Paint
Packing Group	3
Special Provisions	II
	Not regulated for ground transport when shipped 1000 lbs or less.

**TDG**

Not regulated.

**MEX**

Not regulated.

**ICAO (air)**

Not regulated.

**IATA**

Not regulated.

**IMDG**

Not regulated.

<u>RID</u>	Not regulated.
<u>ADR</u>	Not regulated.
<u>ADN</u>	Not regulated.

## 15. REGULATORY INFORMATION

### International Inventories

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Zinc - 7440-66-6	1.0
Xylene, mixed isomers, pure - 1330-20-7	1.0

#### SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	Yes

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6	-	X	X	-
Xylene, mixed isomers, pure 1330-20-7	100 lb	-	-	X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Zinc 7440-66-6	1000 lb	-	RQ 454 kg final RQ RQ 1000 lb final RQ
Xylene, mixed isomers, pure 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Silica, quartz - 14808-60-7	Carcinogen

#### U.S. State Right-to-Know Regulations



Chemical Name	New Jersey	Massachusetts	Pennsylvania
VM & P Naphtha 8032-32-4	X	X	X
Zinc 7440-66-6	X	X	X
Xylene, mixed isomers, pure 1330-20-7	X	X	X
Silica, quartz 14808-60-7	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 2	Flammability 3	Instability 1	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2	Flammability 3	Physical hazards 1	Personal protection X

<b>Prepared By</b>	Prepared by Adam Dunn
<b>Issue Date</b>	29-May-2015
<b>Revision Date</b>	27-Dec-2018

**Revision Note**  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**