

This safety data sheet complies with the requirements of: GB/T 17519-2013

**Issue Date** 02-Jun-2018**Revision Date** 21-Dec-2018**Version** 3**Product identifier****Product Name** Silicone Roof Coating - Low Solids**Other means of identification****Product Code** LUCAS 8400**Synonyms** None**Recommended use of the chemical and restrictions on use****Recommended Use** Reflective Roof Coating.**Uses advised against** No information available**Details of the supplier of the safety data sheet****Manufacturer Address** R.M. Lucas Company  
3211 South Wood Street  
Chicago, Illinois 60608  
(773) 523-4300**Emergency telephone number****Emergency Telephone** Call CHEMTREC Day or Night:  
Within USA and Canada: 1-800 424-9300**2. HAZARDS IDENTIFICATION****Classification****OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 3

**Label elements****Emergency Overview****Danger****Hazard statements**

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor



<b>Appearance</b> No information available	<b>Physical state</b> Liquid	<b>Odor</b> Peppermint Solvent
--	------------------------------	--------------------------------

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

Unknown acute toxicity 100% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Chemical Name	CAS No.	Weight-%	Trade Secret
Silica, quartz	14808-60-7	30 - 40%	*
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	30 - 40%	*
Dimethyl siloxane, hydroxy-terminated	70131-67-8	30 - 40%	*
Titanium Dioxide	13463-67-7	0 - 10%	*
Methyl Tris (MEKO) Silane	22984-54-9	0 - 10%	*

### 4. FIRST AID MEASURES

**Description of first aid measures**

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

**Skin contact** Wash skin with soap and water.

**Inhalation** Remove to fresh air.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

No information available.

#### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas.

### Environmental precautions

**Environmental precautions** See Section 12 for additional ecological information.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible materials** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Silica, quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/( %SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/( %SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

Mineral Spirits (with < 0.1% Benzene) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Titanium Dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale

**Appropriate engineering controls**

**Engineering Controls**                      Showers  
   Eyewash stations  
   Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      No special technical protective measures are necessary.

**Skin and body protection**                No special technical protective measures are necessary.

**Respiratory protection**                    If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations**        Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	Peppermint Solvent
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	No information available		
<b>Melting point/freezing point</b>	-94		
<b>Boiling point / boiling range</b>	154 310		
<b>Flash point</b>	103		
<b>Evaporation rate</b>	.1		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limit in Air</b>		Combustible liquid	
<b>Upper flammability limit:</b>	7.0		
<b>Lower flammability limit:</b>	1.6		
<b>Vapor pressure</b>	.3		
<b>Vapor density</b>	5.3		
<b>Specific Gravity</b>	1.2		
<b>Water solubility</b>	No information available		
<b>Solubility in other solvents</b>	No information available		
<b>Partition coefficient</b>	No information available		
<b>Autoignition temperature</b>	626		
<b>Decomposition temperature</b>	No information available		
<b>Kinematic viscosity</b>	No information available		
<b>Dynamic viscosity</b>	No information available		
<b>Explosive properties</b>	No information available		
<b>Oxidizing properties</b>	No information available		
<b>Other Information</b>			
<b>Softening point</b>	No information available		
<b>Molecular weight</b>	No information available		
<b>VOC Content (%)</b>	Less than 270 g/l.		
<b>Density</b>	No information available		
<b>Bulk density</b>	No information available		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Conditions to avoid

Extremes of temperature and direct sunlight.

### Incompatible materials

None known based on information supplied.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	No data available.
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin contact</b>	No data available.
<b>Ingestion</b>	No data available.

### Component Information

\* No significant exposure to Crystalline Silica (Quartz) is thought to occur during the use of products in which Crystalline Silica (Quartz) is bound to other materials, such as in paints and coatings. As one reference, see California Office of Health Hazard Assessment at: [http://www.oehha.org/prop65/CRNR\\_notices/safe\\_use/sylicasud2.html](http://www.oehha.org/prop65/CRNR_notices/safe_use/sylicasud2.html) \* The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states: "Operators in user industries who handle fluffy or pelleted Carbon Black during rubber, paint and ink production are expected to have significantly lower exposures to Carbon Black than workers in Carbon Black production. Other workers in user industries who handle it occasionally have little opportunity for exposure. And further... "End-users of these products (rubber, ink or paint) are unlikely to be exposed to airborne Carbon Black particles, which are bound within the product matrix."

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dimethyl siloxane, hydroxy-terminated 70131-67-8	> 15400 mg/kg ( Rat )	> 16 mL/kg ( Rabbit )	> 8750 mg/m <sup>3</sup> ( Rat ) 7 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed

any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Silica, quartz 14808-60-7	A2	Group 1	Known	X
Titanium Dioxide 13463-67-7	-	Group 2B	-	X

**Reproductive toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration hazard** Risk of serious damage to the lungs (by aspiration). May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

**ATEmix (oral)** 14,311.40  
**ATEmix (dermal)** 15,967.95

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging** Do not reuse container.

**14. TRANSPORT INFORMATION**

**DOT** (If shipped in NON BULK packaging by ground transport)

**Proper shipping name** Combustible liquid, n.o.s. (Mineral Spirits)  
**Hazard Class** 3  
**Packing Group** III

**TDG** Not regulated.

**UN/ID no.** NA 1993  
**Proper shipping name** Combustible liquid, n.o.s  
**Hazard Class** 3  
**Packing Group** III

**ICAO (air)** Not regulated.

**RID** Not regulated.

**ADR** Not regulated.

**ADN** Not regulated.

## 15. REGULATORY INFORMATION

### International Inventories

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

<b>Acute health hazard</b>	No
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

#### CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Silica, quartz - 14808-60-7	Carcinogen
Titanium Dioxide - 13463-67-7	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Silica, quartz 14808-60-7	X	X	X
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<u>NFPA</u>	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X

<p><b>Prepared By</b>  <b>Issue Date</b>  <b>Revision Date</b>  <b>Revision Note</b>                  No information available</p>	<p>Prepared by Adam Dunn                  02-Jun-2018                  21-Dec-2018</p>
--	--

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**