



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 12400 S. Laramie Ave. Alsip, IL 60803 (773) 523-4300 rmlucas.com

#5025 SPLICE WASH LOW VOC

PRODUCT DESCRIPTION

Lucas #5025 Splice Wash is a fast drying solvent cleaner intended for cleaning and preparing seam areas of single-ply roofing membranes for bonding. #5025 is compatible with EPDM, PVC and TPO roofing.

Lucas #5025 is 100% pure refined aliphatic hydrocarbon and VOC exempt ketone solvent with a fast evaporation rate. #5025 is a low VOC formula.

APPLICATION

Apply #5025 to the seam area with a clean rag. Wipe the area until all surface contamination is removed. Allow the splice wash to dry completely before bonding the seam. Dry time will vary but is generally five to ten minutes.

Clean up: NA

Shelf Life: Two years from the date of manufacture.

WARNING! FLAMMABLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.



#5025 SPECIFICATION

Viscosity	ASTM D 2196	50 cps
Solids by Weight	ASTM D 1644	0%
Solids by Volume	ASTM D 2697	0%
Weight per Gallon	ASTM D 1475	6.6 lbs.
Flash Point	ASTM D56	-4 F (-20° C)
VOC (7000 Standard)	EPA 24	< 250 g/l

VOC compliant in all 50 states and Canada.

Container Sizes: 14 oz. aerosol spray, 1, 5 gallon

Colors: Clear

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.