



#778

ALUMINUM FLASHING CEMENT PREMIUM GRADE

PRODUCT DESCRIPTION

Lucas #778 Aluminum Flashing Cement is a premium quality trowel-applied Flashing Cement used to repair or rebuild roof flashings at parapet walls, gravel stops, stacks, vents, monitors and similar applications. #778 may be used with fiberglass, polyester fabrics or roll roofing for permanent repairs. #778 is aluminum colored to better match the color of aluminum coated and metal roofs. The reflective aluminum pigments also protect the asphalt binder from UV degradation.

#778 Flashing Cement is manufactured from higher softening point asphalt, petroleum solvents, aluminum pigment and reinforcing fibers. It applies fast and smooth and breaks cleanly off the trowel without stringing.

APPLICATION

The surface to be repaired must be clean, dry and free of debris. Apply #778 Aluminum Flashing Cement evenly with a pointed roofer's trowel or gloved hand. #778 should be applied 1/8 to 1/4 of an inch thick and may be reinforced with polyester fabric to strengthen the repair. When making a permanent repair to a blister, open up the area and allow it to dry thoroughly.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

#778 SPECIFICATION

Viscosity	ASTM D 2196	500,000 cps
Solids by Weight	ASTM D 1644	76%
Solids by Volume	ASTM D 2697	73%
% Asphalt	ASTM D 6511	35%
Weight Per Gallon	ASTM D 1147	9.6 lbs.
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<275 g/l

Container Sizes: 5 gallon

Colors: Aluminum

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

6-2018

