



LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 3211 S. Wood St. Chicago, IL 60608 (773) 523-4300 rmlucas.com

#488 2% NEOPRENE ASPHALT PAVER BLOCK ADHESIVE SOLVENT-BASED

PRODUCT DESCRIPTION

#488 2% Neoprene Asphalt Paver Block Adhesive is a heavy mastic intended for installing concrete pavers over poured in place concrete surfaces. #488 is a solvent-based product and may be used in colder temperatures than water-based products. #488 is available in trowel and brush grades.

Lucas #488 2% Neoprene Asphalt Paver Block is manufactured from high softening point refined asphalts, Neoprene rubber, reinforcing fibers and rheological clays.

APPLICATION

#488 2% Neoprene Asphalt Paver Block Adhesive may only be applied when temperatures are below freezing but material temperature should be a minimum of 50°F for ease of application. Surface must be clean. Apply with a notched trowel or squeegee at the rate 2 gallons per 100 sq. ft. Allow the adhesive to partially set so that it is tacky but not dry, then embed the pavers. Uneven surfaces will require higher rates of application.

All application rates are approximate and are derived from our laboratory tests and reported field experience. It is left to the judgment of the applicator to assure that sufficient material is applied for adhesion and coverage. Over application and colder temperatures may extend drying time.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

#488 SPECIFICATION

Viscosity	ASTM D 2196	15,000 cps
Solids by Weight	ASTM D 1644	76%
Solids by Volume	ASTM D 2697	59%
% Asphalt	ASTM D 6511	69%
% Neoprene	NA	2%
% Fibers	NA	10%
Weight Per Gallon	ASTM D 1147	8.3 lbs.
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<250 g/l

Seasonal Grades: Mid-Season only.

Container Sizes: 5, 55, 275 gallon

Colors: Black

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.