



#8750 RELEASABLE FLOORING ADHESIVE

PRODUCT DESCRIPTION

Lucas #8750 Releasable Flooring Adhesive is a water based contact adhesive for securing PVC backed carpet tiles and vinyl flooring. Fast drying with aggressive tack, #8700 bonds instantly without the risk of fire associated with flammable solvent based adhesives. VOC compliant in all of North America.

Lucas #8750 is manufactured from strong, elastic, plasticizer resistant polymer resin and special additives in a water vehicle. #8750 exhibits permanent surface tack.

APPLICATION

The surface must be clean and dry. Temperature must be a minimum of 40°F with humidity of less than 90% for proper curing. Apply #8750 at the rate of one gallon per 100 square feet. Porous surfaces will require more adhesive. Higher application rates will extend the adhesive's cure time. The adhesive should be applied with a 1/2 inch nap roller or suitable spray equipment. Allow the adhesive to dry completely. The color of the adhesive will change from light to dark blue when the adhesive is fully dry.

Lay tiles onto surface and press or roll with a weighted roller to ensure adhesion.

#8750 may be used as a non-releasable wet lay adhesive for carpet padding, conventional rolled carpet and artificial turf. It is suitable for indoor and outdoor applications.

Clean up: Clean up wet adhesive with soap & water.

Shelf Life: Two years from the date of manufacture.

CAUTION: Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read SDS prior to use.

#8750 SPECIFICATION

Viscosity	ASTM D 2196	20,000 cps
Solids by Weight	ASTM D 1644	50%
Solids by Volume	ASTM D 2697	48 %
Weight Per Gallon	ASTM D 1147	8.6 lbs.
Flash Point	ASTM D 56	NA
VOC	EPA 24	0 g/l

Container Sizes: 5, 55, 275 gallon

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. LIMITATION OF LIABILITY: In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

6-2018

