



#202 ASPHALT EMULSION UNDERBODY

PRODUCT DESCRIPTION

#202 Asphalt Emulsion Coating is a water-based asphalt emulsion, which is modified for superior adhesion to metal, flexibility and corrosion protection. This medium viscosity underbody coating is reinforced with mineral fillers and corrosion inhibitors to produce a tough, tight black film which resists mud cracking. It contains no volatile organic compounds and is easily sprayed to provide sound deadening.

Lucas #202 Asphalt Undercoat is primarily intended to provide protection for automotive, truck and trailer underbodies. It may be used on any metal or wood surfaces where corrosion and sound deadening properties are desired.

APPLICATION

Lucas #202 Asphalt Emulsion Coating may only be applied when temperatures are expected to remain above 50°F for the next 24 hours. Surface must be clean. Surface condition is a critical factor in achieving a successful application. Care should be taken to protect areas which are not intended to be coated. Catalytic converters, transmission heat shields, drive shafts, exhaust manifolds, break drums, oil pans and disc brakes are areas which should not be coated.

Application may be made through the use of conventional systems or airless spray systems. Coverage rates may vary based on porosity of surface, material temperature and application technique. Typical coverage rate is 80 square feet per gallon which yields 20 mils of wet film.

Clean Up: Wet coating soap and water. Dry coating Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

CAUTION: Avoid prolonged contact with or inhalation of fumes. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

#202 SPECIFICATION

Solids by Weight	ASTM D 1644	55%
Solids by Volume	ASTM D 2697	50%
Flash Point	ASTM D 56	NA

Container Sizes: 5, 55 gallon

Colors: Black

TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.

6-2018

BODY BUILT BY
B. HEINIG
1464-1466 WEBSTER AV.