



# LUCAS Professional Coatings, Sealants & Adhesives

R.M. Lucas Co. 12400 S. Laramie Ave. Alsip, IL 60803 (773) 523-4300 rmlucas.com

## #302 ROOF & FOUNDATION COATING – PREMIUM NON-FIBRATED

### #302 SPECIFICATION

Viscosity	ASTM D 2196	5,000 cps
Solids by Weight	ASTM D 1644	73%
Solids by Volume	ASTM D 2697	72%
% Asphalt	ASTM D 6511	73%
Weight Per Gallon	ASTM D 1147	7.9 lbs.
Flash Point	ASTM D 56	103°F / 39°C
VOC	EPA 24	<270 g/l

#### PRODUCT DESCRIPTION

Lucas #302 Roof & Foundation Coating – Premium Non-Fibrated provides an economical means of recoating and preserving smooth-surface asphalt roofs. Periodic recoating of otherwise sound built-up roofing felts can prolong service life many years. This product is not intended for use over tar or asphalt and gravel roofs. Please refer to our #010 for tar roofs and #713 for asphalt and gravel roofs. #302 is also recommended as a faster drying dampproof coating for new poured foundation walls.

Lucas #302 is formulated from refined, higher softening point asphalt and petroleum solvents. Consistency is maintained to provide easy brushing qualities. Application of #302 produces a faster setting film that allows foot traffic sooner than standard quality products. All Lucas asphalt roof coatings are ready to use and do not require special preparation before use.

#### APPLICATION

Surface to be coated must be clean and dry. Weak, broken, cracked or blistered areas of the roof and flashings must be repaired prior to coating with #302. Blisters, which are caused by trapped moisture, must be opened and dried, then resealed using glass membrane and flashing cement. Moisture trapped between plies of a roof will eventually reappear as a blister or a leak. Seal form ties on foundation walls with Lucas Form Tie Cement. Apply #302 evenly, as it comes from the container with any appropriate tool, preferably, a four knot roofing brush, at the rate of approximately one to two gallons per 100 square feet. Do not allow foot traffic until the coating is fully cured.

Clean Up: Lucas #125 Safe Solve™.

Shelf Life: 2 years minimum.

**WARNING! COMBUSTIBLE LIQUID AND VAPOR.** Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

Seasonal Grades: Mid-Season only.

Container Sizes: 5, 55 gallon, bulk

Colors: Black

This product is Florida Building Code approved.



TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

**NOTE:** Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.