

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 08-Sep-2023 Revision Date 08-Sep-2023 Version 1

Product identifier

Product Name Flame resistant Acrylic Topcoat

Other means of identification

Product Code LUCAS 1000FR Synonyms Roof Coating

Recommended use of the chemical and restrictions on use

Recommended UseWhite Roof Coating. Reflective Roof Coating. **Uses advised against**For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company

12400 South Laramie Ave Alsip, Illnois 60803 (773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

Label elements

Emergency Overview

Danger

Hazard statements

May cause cancer



Appearance Viscous Physical state Liquid Odor Low

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Mixture

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

White Roof Coating. Common name **Synonyms** Roof Coating.

Chemical nature Mixture of moisture reactive polymers, plasticizers and fillers.

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|--------------------|------------|----------|--------------|
| Acrylic Co-Polymer | 25035-69-2 | 30 - 40% | * |
| Aluminum Hydroxide | 21645-51-2 | 30 - 40% | * |
| Water | 7732-18-5 | 20 - 30% | * |
| Titanium Dioxide | 13463-67-7 | 10 - 20% | * |
| Ethylene glycol | 107-21-1 | 0 - 10% | * |

4. FIRST AID MEASURES

Description of first aid measures

Under conditions of normal use, no hazards are anticipated which require special first aid **General advice**

measures.

In the case of contact with eyes, rinse immediately with plenty of water and seek medical Eye contact

advice.

Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash Skin contact

contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a

physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with

breathing is experienced, get medical attention immediately.

Ingestion Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical

attention immediately.

First aider: Pay attention to self-protection!. Self-protection of the first aider

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to physicians

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

N/A.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Not sensitive.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use

personal protective equipment as required.

Other Information Extremely slippery when spilled.

Use personal protection recommended in Section 8. For emergency responders

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous

earth, vermiculite.

Pick up the absorbed material (described just above) and transfer to properly labeled Methods for cleaning up

containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Use only outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing. Keep containers tightly closed in a cool, dry, well-ventilated place.

Strong acids. Strong oxidizing agents. Incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--------------------|----------------------------------|---|--|
| Aluminum Hydroxide | TWA: 1 mg/m³ respirable | - | - |
| 21645-51-2 | particulate matter | | |
| Titanium Dioxide | TWA: 10 mg/m ³ | TWA: 15 mg/m³ total dust | IDLH: 5000 mg/m ³ |
| 13463-67-7 | | (vacated) TWA: 10 mg/m ³ total | TWA: 2.4 mg/m ³ CIB 63 fine |
| | | dust | TWA: 0.3 mg/m ³ CIB 63 ultrafine, |
| | | | including engineered nanoscale |
| Ethylene glycol | STEL: 50 ppm vapor fraction | (vacated) Ceiling: 50 ppm | - |
| 107-21-1 | STEL: 10 mg/m³ inhalable | (vacated) Ceiling: 125 mg/m ³ | |
| | particulate matter, aerosol only | | |
| | TWA: 25 ppm_vapor fraction | | |

Appropriate engineering controls

Engineering Controls None under normal outdoor use conditions.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin and body protection Wear protective gloves and protective clothing that is resistant to chemical penetration.

Respiratory protection No protective equipment is needed under normal use conditions.

General Hygiene Considerations Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated

clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Viscous Odor Low

White Negligible odor. Color Odor threshold

Remarks • Method Property Values

pН 9-10

Melting point/freezing point None / 0 276F None / 32 °F Melting Point is not applicable. Freezing points are

shown. Boiling point / boiling range > 100 212DEG F / 212 °F

Flash point Not applicable 276F / Not Non Flammable

applicable °F

The evaporation rate of the water **Evaporation rate** No data available. Evaporation rate is dependent

component of this emulsion product is upon atmospheric conditions.

Not flammable

dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of

the air-water surface; 4) The temperature of the air. N/A

Non Flammable

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: Not applicable Lower flammability limit: Not applicable

LUCAS 1000FR Flame resistant Acrylic Topcoat

No data available.

Revision Date 08-Sep-2023

Vapor pressure 2.33 (kPa) @ 20 °C

Vapor density 5.3 Where: Air = 1 at 68 degrees F (20 degrees C)

Specific Gravity 1.34 Water = 1g/ml

Water solubility Dispersible

Solubility in other solvents Soluble in aromatic and aliphatic

solvents.

Partition coefficient N/A

Autoignition temperature 330 276F / 626 °F

Decomposition temperature N/A
Kinematic viscosity N/A
Dynamic viscosity N/A

Explosive properties Not an explosive

Oxidizing properties None

Other Information

Softening point Not applicable Molecular weight N/A

VOC Content (%)

Density

Bulk density

Less than 50 g/l

11.0 to 11.4 lb/gal

Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

None known for product as a whole.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Toxicological testing has not been conducted for this product overall. Available toxicological

data for individualing redients are summarized below.

Inhalation Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes. Contact with eyes may cause irritation.

Skin contact May cause irritation.

Ingestion If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected

route of exposure.

Component Information * No significant exposure to Crystalline Silica (Quartz) is thought to occur during the use of

products in which Crystalline Silica (Quartz) is bound to other materials, such as in paints and coatings. As one reference, see California Office of Health Hazard Assessment at: http://www.oehha.org/prop65/CRNR_notices/safe_use/sylicasud2.html

The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states "No significant exposure to primary particles of Talc is thought to occur during the use of products in which Talc is bound to other materials, such as in paints."

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--------------------------------|----------------------|-----------------------|-----------------|
| Aluminum Hydroxide | > 5000 mg/kg (Rat) | - | - |
| 21645-51-2 | | | |
| Water | > 90 mL/kg (Rat) | - | - |
| 7732-18-5 | | | |
| Titanium Dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Ethylene glycol | = 4700 mg/kg (Rat) | = 10600 mg/kg (Rat) | - |
| 107-21-1 | | = 9530 μL/kg (Rabbit) | |

Information on toxicological effects

Symptoms N/A.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Can cause skin irritation.

Serious eye damage/eye irritation Irritat

Irritating to eyes.

Irritation

Irritating to eyes and skin.

Corrosivity Not classified.

Sensitization May cause sensitization of susceptible persons.

Germ cell mutagenicityThis product does not contain any ingredients that cause germ cell mutagenicity.

Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed

any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|------------------|-------|----------|-----|------|
| Titanium Dioxide | - | Group 2B | - | X |
| 13463-67-7 | | · · | | |

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen.

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

None known for product as a whole.

None known for product as a whole.

Teratogenicity None known.

STOT - single exposure N/A.
STOT - repeated exposure N/A.
Aspiration hazard N/A.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 16,437.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

14.75% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|-----------------|---------------------------------|--------------------------------------|--------------------------------|
| Ethylene glycol | 6500 - 13000: 96 h | 14 - 18: 96 h Oncorhynchus mykiss | 46300: 48 h Daphnia magna mg/L |
| 107-21-1 | Pseudokirchneriella subcapitata | mL/L LC50 static | EC50 |
| | mg/L EC50 | 40000 - 60000: 96 h Pimephales | |
| | | promelas mg/L LC50 static | |
| | | 16000: 96 h Poecilia reticulata mg/L | |
| | | LC50 static | |
| | | 27540: 96 h Lepomis macrochirus | |
| | | mg/L LC50 static | |
| | | 40761: 96 h Oncorhynchus mykiss | |
| | | mg/L LC50 static | |
| | | 41000: 96 h Oncorhynchus mykiss | |
| | | mg/L LC50 | |

Persistence and degradability

N/A

Bioaccumulation

N/A.

| Chemical Name | Partition coefficient |
|-----------------|-----------------------|
| Ethylene glycol | -1.93 |
| 107-21-1 | |

Other adverse effects N/A

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable local, regional, national and international

laws and regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

Note: This material is not subject to regulation as a hazardous material for shipping

DOT Not regulated.TDG Not regulated.

MEX Not regulated.

ICAO (air) Not regulated.

<u>IATA</u> Not regulated.

<u>IMDG</u> Not regulated.

RID Not applicable in the United States. Not regulated.

ADR Not applicable in the United States. Not regulated.

ADN Not applicable in the United States. Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

DSL/NDSL All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|-----------------------------------|-------------------------------|
| Ethylene glycol - 107-21-1 | 1.0 |
| SARA 311/312 Hazard Categories | |
| Acute health hazard | No |
| Chronic Health Hazard | No |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|-----------------|--------------------------|----------------|--------------------------|
| Ethylene glycol | 5000 lb | - | RQ 5000 lb final RQ |
| 107-21-1 | | | RQ 2270 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 | |
|-------------------------------|---------------------------|--|
| Titanium Dioxide - 13463-67-7 | Carcinogen | |
| Ethylene glycol - 107-21-1 | Developmental | |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--------------------------------|------------|---------------|--------------|
| Water 7732-18-5 | - | - | X |
| Titanium Dioxide 13463-67-7 | X | X | Х |
| Ethylene glycol 107-21-1 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and Chemical

Properties -

Revision Date 08-Sep-2023

HMIS Health hazards 1 Flammability 0 Physical hazards 0 Personal protection -

Prepared By Prepared by Steve Velten

 Issue Date
 08-Sep-2023

 Revision Date
 08-Sep-2023

Revision Note

Version #1 was not released for public distribution. Version #1 was a test/working document.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet