

# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 05-Sep-2023 Revision Date 05-Sep-2023 Version 1

Product identifier

Product Name Elastomeric Roof Coating

Other means of identification

Product Code LUCAS 1000TC Synonyms Roof Coating

Recommended use of the chemical and restrictions on use

**Recommended Use**White Roof Coating. Reflective Roof Coating. **Uses advised against**For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company

12400 South Laramie Ave Alsip, Illnois 60803 (773) 523-4300

**Emergency telephone number** 

Emergency Telephone Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300

# 2. HAZARDS IDENTIFICATION

## Classification

# **OSHA Regulatory Status**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

#### Label elements

## **Emergency Overview**

# Danger

# Hazard statements

May cause cancer



Appearance Viscous Physical state Liquid Odor Low

# **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response** 

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage** 

Store locked up

**Precautionary Statements - Disposal** 

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

**Mixture** 

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common nameWhite Roof Coating.SynonymsRoof Coating.

**Chemical nature** Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical Name	CAS No.	Weight-%	Trade Secret
Acrylic Co-Polymer	25035-69-2	30 - 40%	*
Calcium Carbonate	1317-65-3	30 - 40%	*
Water	7732-18-5	20 - 30%	*
Titanium Dioxide	13463-67-7	10 - 20%	*
Ethylene glycol	107-21-1	0 - 10%	*

# 4. FIRST AID MEASURES

# **Description of first aid measures**

General advice Under conditions of normal use, no hazards are anticipated which require special first aid

measures.

Eye contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin contact** Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a

physician.

**Inhalation** Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with

breathing is experienced, get medical attention immediately.

Ingestion Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical

attention immediately.

**Self-protection of the first aider** First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

**Symptoms** May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to physicians

#### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

# Specific hazards arising from the chemical

N/A.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

**Explosion data** 

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Not sensitive.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use

personal protective equipment as required.

Other Information Extremely slippery when spilled.

Use personal protection recommended in Section 8. For emergency responders

Environmental precautions

**Environmental precautions** Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous

earth, vermiculite.

Pick up the absorbed material (described just above) and transfer to properly labeled Methods for cleaning up

containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Use only outdoors.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep from freezing. Keep containers tightly closed in a cool, dry, well-ventilated place.

Strong acids. Strong oxidizing agents. Incompatible materials

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate	-	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> total dust
1317-65-3		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m³ total	-
		dust	
		(vacated) TWA: 5 mg/m <sup>3</sup> respirable	
		fraction	
Titanium Dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	_	(vacated) TWA: 10 mg/m³ total	TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine
		dust	TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine,
			including engineered nanoscale
Ethylene glycol	STEL: 50 ppm_vapor fraction	(vacated) Ceiling: 50 ppm	-
107-21-1	STEL: 10 mg/m³ inhalable	(vacated) Ceiling: 125 mg/m <sup>3</sup>	
	particulate matter, aerosol only		
	TWA: 25 ppm vapor fraction		

### Appropriate engineering controls

**Engineering Controls** None under normal outdoor use conditions.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear protective gloves and protective clothing that is resistant to chemical penetration. Skin and body protection

Respiratory protection No protective equipment is needed under normal use conditions.

Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated **General Hygiene Considerations** 

clothing before reuse.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Information on basic physical and chemical properties

Physical state Liquid Appearance Viscous

Odor Low

Color White **Odor threshold** Negligible odor.

Remarks • Method **Property** Values

Not applicable pН

Melting point/freezing point None / 0 276F None / 32 °F Melting Point is not applicable. Freezing points are shown.

Boiling point / boiling range > 100 276F / 212 °F

Flash point Not applicable 276F / Not Non Flammable

applicable °F

**Evaporation rate** The evaporation rate of the water No data available. Evaporation rate is dependent

component of this emulsion product is upon atmospheric conditions. dependent upon: 1) The temperature

of the water at the air-water surface; 2) The humidity of the air; 3) The area of

the air-water surface; 4) The temperature of the air. N/A

Non Flammable Flammability (solid, gas)

# **LUCAS 1000TC Elastomeric Roof Coating**

Not flammable

No data available.

Revision Date 05-Sep-2023

Flammability Limit in Air

**Upper flammability limit:** 

Not applicable Not applicable

Lower flammability limit: Not appl Vapor pressure 2.33 (kP

Vapor pressure2.33 (kPa)@ 20 °CVapor density5.3Where: Air = 1 at 68 degrees F (20 degrees C)

Specific Gravity 1.34 Water = 1g/ml

Water solubility Dispersible

Solubility in other solvents Soluble in aromatic and aliphatic

solvents.

Partition coefficient N/A
Autoignition temperature 330 276F / 626 °F

Decomposition temperature

N/A

Kinematic viscosity

N/A

Dynamic viscosity

N/A

Explosive properties Not an explosive

Oxidizing properties None

**Other Information** 

Softening point Not applicable

Molecular weight N/A

VOC Content (%)

Density

Bulk density

Less than 50 g/l

11.0 to 11.4 lb/gal

Not applicable

# 10. STABILITY AND REACTIVITY

Reactivity

Not applicable Not applicable

**Chemical stability** 

Stable.

**Possibility of Hazardous Reactions** 

None under normal use.

**Hazardous polymerization** Hazardous polymerization does not occur.

**Conditions to avoid** 

None known for product as a whole.

**Incompatible materials** 

Strong acids. Strong oxidizing agents.

**Hazardous Decomposition Products** 

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

# 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Toxicological testing has not been conducted for this product overall. Available toxicological

data for individualing redients are summarized below.

**Inhalation** Avoid breathing vapors or mists.

**Eye contact** Avoid contact with eyes. Contact with eyes may cause irritation.

**Skin contact** May cause irritation.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected

route of exposure.

#### **Component Information**

\* No significant exposure to Crystalline Silica (Quartz) is thought to occur during the use of products in which Crystalline Silica (Quartz) is bound to other materials, such as in paints and coatings. As one reference, see California Office of Health Hazard Assessment at: http://www.oehha.org/prop65/CRNR\_notices/safe\_use/sylicasud2.html

The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states "No significant exposure to primary particles of Talc is thought to occur during the use of products in which Talc is bound to other materials, such as in paints."

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	-	-
7732-18-5			
Titanium Dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			
Ethylene glycol	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)	-
107-21-1		= 9530 μL/kg (Rabbit)	

#### Information on toxicological effects

Symptoms N/A.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Can cause skin irritation.

Serious eye damage/eye irritation Irritating to eyes.

Irritation Irritating to eyes and skin.

Corrosivity Not classified.

**Sensitization** May cause sensitization of susceptible persons.

**Germ cell mutagenicity**This product does not contain any ingredients that cause germ cell mutagenicity.

Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed

any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide	-	Group 2B	-	X
13463-67-7		-		

#### Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen.

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

Developmental Toxicity

None known for product as a whole.

None known for product as a whole.

Teratogenicity None known.

STOT - single exposure N/A.
STOT - repeated exposure N/A.
Aspiration hazard N/A.

# Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

**ATEmix (oral)** 16,437.00

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

14.75% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethylene glycol	6500 - 13000: 96 h	14 - 18: 96 h Oncorhynchus mykiss	46300: 48 h Daphnia magna mg/L
107-21-1	Pseudokirchneriella subcapitata	mL/L LC50 static	EC50
	mg/L EC50	40000 - 60000: 96 h Pimephales	
		promelas mg/L LC50 static	
		16000: 96 h Poecilia reticulata mg/L	
		LC50 static	
		27540: 96 h Lepomis macrochirus	
		mg/L LC50 static	
		40761: 96 h Oncorhynchus mykiss	
		mg/L LC50 static	
		41000: 96 h Oncorhynchus mykiss	
		mg/L LC50	

# Persistence and degradability

N/A.

## **Bioaccumulation**

N/A.

Chemical Name	Partition coefficient
Ethylene glycol	-1.93
107-21-1	

Other adverse effects N/A

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable local, regional, national and international

laws and regulations.

Contaminated packaging Do not reuse container.

# 14. TRANSPORT INFORMATION

**Note:** This material is not subject to regulation as a hazardous material for shipping

DOT Not regulated.TDG Not regulated.

MEX Not regulated.

ICAO (air) Not regulated.

<u>IATA</u> Not regulated.

**IMDG** Not regulated.

RID Not applicable in the United States. Not regulated.

ADR Not applicable in the United States. Not regulated.

**ADN** Not applicable in the United States. Not regulated.

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

**DSL/NDSL** All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Ethylene glycol - 107-21-1	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

# **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene glycol	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

## **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen
Ethylene glycol - 107-21-1	Developmental

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate	X	X	X
1317-65-3			
Water	-	-	X
7732-18-5			
Titanium Dioxide	X	X	X
13463-67-7			

# **LUCAS 1000TC Elastomeric Roof Coating**

Revision Date 05-Sep-2023

Ethylene glycol	X	X	X
107-21-1			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Health hazards 1 Flammability 0 Instability 0 **Physical and Chemical** NFPA\_

Properties -

Health hazards 1 Flammability 0 Physical hazards 0 Personal protection -HMIS

**Prepared By** Prepared by Steve Velten

**Issue Date** 05-Sep-2023 **Revision Date** 05-Sep-2023

**Revision Note** 

Version #1 was not released for public distribution. Version #1 was a test/working document.

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**