



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 06-Sep-2023

Revision Date 06-Sep-2023

Version 1

Product identifier

Product Name Sunscreen Elastomeric Roof Coating

Other means of identification

Product Code LUCAS 1044

Synonyms Roof Coating

Recommended use of the chemical and restrictions on use

Recommended Use White Roof Coating. Reflective Roof Coating.

Uses advised against For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company
12400 South Laramie Ave
Alsip, Illinois 60803
(773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300

2. HAZARDS IDENTIFICATION

Classification


OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 2
-----------------	------------

Label elements

Emergency Overview

Warning		
Hazard statements Suspected of causing cancer		
		
Appearance Viscous	Physical state Liquid	Odor Low

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

• Harmful to aquatic life with long lasting effects

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Mixture

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name	White Roof Coating.
Synonyms	Roof Coating.
Chemical nature	Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical Name	CAS No.	Weight-%	Trade Secret
Calcium Carbonate	1317-65-3	30 - 40%	*
Acrylic Co-Polymer	25035-69-2	30 - 40%	*
Water	7732-18-5	20 - 30%	*
Ethylene glycol	107-21-1	0 - 10%	*
Ester Alcohol	25265-77-4	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Under conditions of normal use, no hazards are anticipated which require special first aid measures.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin contact	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

N/A.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Not sensitive.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

Other Information Extremely slippery when spilled.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Use only outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep from freezing. Keep containers tightly closed in a cool, dry, well-ventilated place.
Incompatible materials	Strong acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Ethylene glycol 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-

Appropriate engineering controls

Engineering Controls None under normal outdoor use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing that is resistant to chemical penetration.
Respiratory protection	No protective equipment is needed under normal use conditions.

General Hygiene Considerations Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid	Odor	Low
Appearance	Viscous	Odor threshold	Negligible odor.
Color	White Pale tan		
Property	Values	Remarks • Method	
pH	No applicable		
Melting point/freezing point	None / 0 276F None / 32 °F	Melting Point is not applicable. Freezing points are shown.	
Boiling point / boiling range	> 100 276F / 212 °F		
Flash point	Not applicable 276F / Not applicable °F	Non Flammable	
Evaporation rate	The evaporation rate of the water component of this emulsion product is dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of the air-water surface; 4) The temperature of the air. N/A	No data available. Evaporation rate is dependent upon atmospheric conditions.	
Flammability (solid, gas)	Non Flammable		
Flammability Limit in Air		Not flammable	
Upper flammability limit:	Not applicable		

Lower flammability limit:	Not applicable	
Vapor pressure	2.33 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Specific Gravity	1.4	Water = 1g/ml
Water solubility	Dispersible	
Solubility in other solvents	Soluble in aromatic and aliphatic solvents.	
Partition coefficient	N/A	No data available.
Autoignition temperature	330 276F / 626 °F	
Decomposition temperature	N/A	
Kinematic viscosity	N/A	
Dynamic viscosity	100,000	
Explosive properties	Not an explosive	
Oxidizing properties	None	

Other Information

Softening point	Not applicable
Molecular weight	N/A
VOC Content (%)	Less than 50 g/l
Density	11.4 to 11.8 lb/gal
Bulk density	Not applicable

10. STABILITY AND REACTIVITY**Reactivity**

Not applicable Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

None known for product as a whole.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Product Information	Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.
Inhalation	Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin contact	May cause irritation.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Component Information

* No significant exposure to Crystalline Silica (Quartz) is thought to occur during the use of products in which Crystalline Silica (Quartz) is bound to other materials, such as in paints and coatings. As one reference, see California Office of Health Hazard Assessment at: http://www.oehha.org/prop65/CRNR_notices/safe_use/sylicasud2.html
The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states "No significant exposure to primary particles of Talc is thought to occur during the use of products in which Talc is bound to other materials, such as in paints."

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
Ethylene glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat) = 9530 µL/kg (Rabbit)	-
Ester Alcohol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	> 3.55 mg/L (Rat) 6 h

Information on toxicological effects

Symptoms N/A.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Can cause skin irritation.
Serious eye damage/eye irritation Irritating to eyes.
Irritation Irritating to eyes and skin.
Corrosivity Not classified.
Sensitization May cause sensitization of susceptible persons.
Germ cell mutagenicity This product does not contain any ingredients that cause germ cell mutagenicity.
Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
 A1 - *Known Human Carcinogen*
 A2 - *Suspected Human Carcinogen*
 A3 - *Animal Carcinogen*
 A4 - *Not Classifiable as a Human Carcinogen*
 IARC (International Agency for Research on Cancer)
 Group 1 - *Carcinogenic to Humans*
 Group 2A - *Probably Carcinogenic to Humans*
 Group 2B - *Possibly Carcinogenic to Humans*
 Group 3 - *Not classifiable as a human carcinogen.*
 NTP (National Toxicology Program)
 Known - *Known Carcinogen*
 Reasonably Anticipated - *Reasonably Anticipated to be a Human Carcinogen*
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - *Present*

Reproductive toxicity None known for product as a whole.
Developmental Toxicity None known for product as a whole.
Teratogenicity None known.
STOT - single exposure N/A.
STOT - repeated exposure N/A.
Aspiration hazard N/A.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral) 14,580.37 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

14.75% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea

Ester Alcohol 25265-77-4	18.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	30: 96 h Pimephales promelas mg/L LC50	95: 96 h Daphnia magna mg/L LC50
Ethylene glycol 107-21-1	6500 - 13000: 96 h Pseudokirchneriella subcapitata mg/L EC50	14 - 18: 96 h Oncorhynchus mykiss m/L LC50 static 40000 - 60000: 96 h Pimephales promelas mg/L LC50 static 16000: 96 h Poecilia reticulata mg/L LC50 static 27540: 96 h Lepomis macrochirus mg/L LC50 static 40761: 96 h Oncorhynchus mykiss mg/L LC50 static 41000: 96 h Oncorhynchus mykiss mg/L LC50	46300: 48 h Daphnia magna mg/L EC50

Persistence and degradability

N/A.

Bioaccumulation

N/A.

Chemical Name	Partition coefficient
Ethylene glycol 107-21-1	-1.93
Ester Alcohol 25265-77-4	3.47

Other adverse effects

N/A

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION**Note:**

This material is not subject to regulation as a hazardous material for shipping

DOT

Not regulated.

TDG

Not regulated.

MEX

Not regulated.

ICAO (air)

Not regulated.

IATA

Not regulated.

IMDG

Not regulated.

RID

Not applicable in the United States. Not regulated.

ADR

Not applicable in the United States. Not regulated.

ADN

Not applicable in the United States. Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

DSL/NDSL All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Ethylene glycol - 107-21-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene glycol 107-21-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethylene glycol - 107-21-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Water 7732-18-5	-	-	X
Ethylene glycol 107-21-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

