



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 05-Sep-2023

Revision Date 05-Sep-2023

Version 1

Product identifier

Product Name ACRYLIC SEALANT WHITE

Other means of identification

Product Code LUCAS 1500

Synonyms SEALANT

Recommended use of the chemical and restrictions on use

Recommended Use White acrylic mastic used to repair roofs and seal metal roof fasteners prior to coating with white elastomeric roof coatings.

Uses advised against For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address R.M. Lucas Company
12400 South Laramie Ave
Alsip, Illinois 60803
(773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity

Category 2

Label elements

Emergency Overview

Warning

Hazard statements

Suspected of causing cancer



Appearance Viscous

Physical state Liquid Paste/Gel

Odor Low

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance****Mixture**

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name

Acrylic White Mastic.

Synonyms

SEALANT.

Chemical nature

Mixture of moisture reactive polymers, plasticizers and fillers.

Chemical Name	CAS No.	Weight-%	Trade Secret
Calcium Carbonate	1317-65-3	10 - 20%	*
Titanium Dioxide	13463-67-7	0 - 10%	*
Amorphous Silica (Silicon Dioxide)	7631-86-9	0 - 10%	*
Aluminum Hydroxide	21645-51-2	0 - 10%	*

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Under conditions of normal use, no hazards are anticipated which require special first aid measures.

Eye contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin contact

Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.

Ingestion

Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.

Self-protection of the first aider

First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

N/A.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Not sensitive.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

Other Information Extremely slippery when spilled.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Use only outdoors.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing. Keep containers tightly closed in a cool, dry, well-ventilated place.

Incompatible materials Strong acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(%) SiO ₂ mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³
Aluminum Hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable particulate matter	-	-

Appropriate engineering controls

Engineering Controls None under normal outdoor use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing that is resistant to chemical penetration.

Respiratory protection No protective equipment is needed under normal use conditions.

General Hygiene Considerations Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid Paste/Gel	Odor	Low
Appearance	Viscous	Odor threshold	Negligible odor.
Color	White		
Property	Values	Remarks • Method	
pH	9.0		
Melting point/freezing point	None / 0 276F None / 32 °F	Melting Point is not applicable. Freezing points are shown.	
Boiling point / boiling range	> 100 276F / 212 °F		
Flash point	Not applicable 276F / Not applicable °F	Non Flammable	
Evaporation rate	The evaporation rate of the water component of this emulsion product is	No data available. Evaporation rate is dependent upon atmospheric conditions.	

	dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of the air-water surface; 4) The temperature of the air. N/A	
Flammability (solid, gas)	Non Flammable	
Flammability Limit in Air		Not flammable
Upper flammability limit:	Not applicable	
Lower flammability limit:	Not applicable	
Vapor pressure	2.33 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Specific Gravity	1.38	Water = 1g/ml
Water solubility	Dispersible	
Solubility in other solvents	Soluble in aromatic and aliphatic solvents.	
Partition coefficient	N/A	No data available.
Autoignition temperature	330 276F / 626 °F	
Decomposition temperature	N/A	
Kinematic viscosity	N/A	
Dynamic viscosity	N/A	
Explosive properties	Not an explosive	
Oxidizing properties	None	

Other Information

Softening point	Not applicable
Molecular weight	N/A
VOC Content (%)	Less than 50 g/l
Density	11.4 to 11.6 lb/gal
Bulk density	Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

None known for product as a whole.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Inhalation

Avoid breathing vapors or mists.

Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin contact	May cause irritation.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Component Information The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states "No significant exposure to primary particles of Talc is thought to occur during the use of products in which Talc is bound to other materials, such as in paints."

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Amorphous Silica (Silicon Dioxide) 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
Aluminum Hydroxide 21645-51-2	> 5000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms N/A.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Can cause skin irritation.
Serious eye damage/eye irritation	Irritating to eyes.
Irritation	Irritating to eyes and skin.
Corrosivity	Not classified.
Sensitization	May cause sensitization of susceptible persons.
Germ cell mutagenicity	This product does not contain any ingredients that cause germ cell mutagenicity.
Carcinogenicity	The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide 13463-67-7	-	Group 2B	-	X
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	Group 3	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen
A4 - Not Classifiable as a Human Carcinogen
 IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not classifiable as a human carcinogen.
 NTP (National Toxicology Program)
Known - Known Carcinogen
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive toxicity	None known for product as a whole.
Developmental Toxicity	None known for product as a whole.
Teratogenicity	None known.
STOT - single exposure	N/A.
STOT - repeated exposure	N/A.
Aspiration hazard	N/A.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

14.75% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

N/A.

Bioaccumulation

N/A.

Other adverse effects

N/A

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION**Note:**

This material is not subject to regulation as a hazardous material for shipping

DOT

Not regulated.

TDG

Not regulated.

MEX

Not regulated.

ICAO (air)

Not regulated.

IATA

Not regulated.

IMDG

Not regulated.

RID

Not applicable in the United States. Not regulated.

ADR

Not applicable in the United States. Not regulated.

ADN

Not applicable in the United States. Not regulated.

15. REGULATORY INFORMATION**International Inventories****TSCA**

All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

DSL/NDSL

All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen
Amorphous Silica (Silicon Dioxide) - 7631-86-9	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 1	Flammability 1	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection -

Prepared By	AIM Administrative Services Department
Issue Date	05-Sep-2023
Revision Date	05-Sep-2023
Revision Note	N/A

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet