



#8015 TPO PRIMER

PRODUCT DESCRIPTION

Lucas #8015 TPO Primer is an adhesion promoter intended to aid adhesion of 100% silicone and silane-terminated polyurethane coatings and sealants to new and aged TPO roofing membranes.

This product is manufactured from a fast-evaporating solvent carrier and adhesive resins. A blue pigment is added to the standard product so that the applicator can better gauge application rates.

APPLICATION

All surfaces must be clean and completely dry. Apply #8015 with a short nap roller or brush at the rate of one gallon per 800-1000 sq. ft. Applications should be as thin as possible. Allow 2-4 hours before applying coatings or sealants.

The preceding directions are basic guidelines only. Please read and understand the complete Lucas Guide Specification for this product for the intended application. The Guide Specification is available from techsupport@rmlucas.com

Clean Up: Tools and other equipment can be cleaned with mineral spirits. Take necessary precautions when handling combustible materials.

Storage: Keep from freezing. Keep out of direct sunlight. Do not heat or thin. Store between 40°F and 95°F. High temperatures and high humidity during storage will shorten the product's shelf life.

Shelf Life: 2 years from the date of manufacture.

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Contains petroleum distillates. Keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. Read SDS prior to use. For professional use only. Emergency phone number 1-800-424-9300.

#8015 SPECIFICATION

Viscosity	ASTM D 2196	50 cps
Solids by Weight	ASTM D 1644	2%
Solids by Volume	ASTM D 2697	2%
Weight Per Gallon	ASTM D 1147	11.1 lbs.
Flash Point	ASTM D 56	105°F / 41°C
VOC	EPA 24	< 100 g/l

Container Sizes: 1 & 5 gallon

Colors: Blue



TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT AS SET FORTH BELOW, SELLER MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THE GOODS HEREIN SOLD. THERE ARE NO OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED BEYOND THE TERMS SET FORTH ON THE FACE HEREOF. NO EMPLOYEE OR AGENT OF SELLER IS AUTHORIZED TO ALTER THE TERMS HEREOF.

Seller warrants that this product shall be free of any defect in material or workmanship under normal use for a period of ONE YEAR from the date of purchase. This warranty does not extend to any defect or failure caused by misuse and/or incorrect application. **LIMITATION OF LIABILITY:** In the event of a defect or failure falling under this warranty, Buyers sole remedy shall be refund of the purchase price or replacement of the defective material, at Seller's option. Under no circumstances shall Seller be liable for any losses or damages caused by this product, whether direct, indirect, special, incidental or consequential damages, whether based on contract, tort (including negligence) or any other legal theory.

NOTE: Some or all of the foregoing may not apply or may be invalid under the laws applicable to Buyer's purchase or claim. Consult local law to determine the applicability of any of the foregoing in the event of any defect or failure of this product.