

# **SAFETY DATA SHEET**

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 31-Jan-2025 Version 1

### 1. Identification

**Product identifier** 

Product Name Lucas 6500V White

Other means of identification

Product Code LUCAS 6500V WHITE

Synonyms All Weather Flashing Cement

Recommended use of the chemical and restrictions on use

Recommended Use Used for flashing, sealing and repairing metal roofs and trailers, built up roofing, modified

bitumen, TPO, and other single-ply systems.

**Restrictions on use** For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address

R.M. Lucas Company 12400 South Laramie Ave Alsip, Illnois 60803 (773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300

# 2. Hazard(s) identification

### Classification

Flammable liquids	Category 3
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1

### Hazards not otherwise classified (HNOC)

Not applicable.

### Label elements



#### Danger

#### Hazard statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

### **Precautionary Statements - Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/clothing and eye/face protection.

Use only outdoors or in a well-ventilated area.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Do not breathe dust/fume/gas/mist/vapors/spray.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/.?/equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Keep cool.

### **Precautionary Statements - Response**

Specific treatment (see first aid information on this label).

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see .? on this label).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

In case of fire: Use CO2, dry chemical, or foam to extinguish.

### **Precautionary Statements - Storage**

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant.

### Unknown acute toxicity

97 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

### Other Information

No information available.

# 3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Common name Sealant and Caulk.

**Synonyms** All Weather Flashing Cement.

Chemical nature Organic solvents and additives.

Chemical name	CAS No.	Weight-%	Trade secret
Hydrocarbon Resin	68132-00-3	5-25	*
Solvent Naphtha	64742-95-6	10-30	*
Styrene/Butadiene Copolymer	66070-58-4	5-25	*
Hydrated Aluminum-Magnesium Silicate	12174-11-7	5-25	*
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	10-20	*
Titanium Dioxide	13463-67-7	0-10	*
Polyethylene homopolymer	9002-88-4	0-10	*
Solvent Blend	Trade secret	0-10	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

#### **Description of first aid measures**

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

**Inhalation** Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic

reactions see a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin,

eyes or clothing. Avoid breathing vapors or mists.

### Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May

cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically. Because of the

danger of aspiration, emesis or gastric lavage should not be employed unless the risk is

justified by the presence of additional toxic substances.

# 5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media**Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or

contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors

and fumes.

**Explosion data** 

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing

vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. Handling and storage

#### Precautions for safe handling

### Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eves or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

# 8. Exposure controls/personal protection

#### Control parameters

#### **Exposure Limits**

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Hydrated Aluminum-Magnesium	TWA: 1 mg/m <sup>3</sup> respirable	-	-
Silicate	particulate matter		
12174-11-7			
Mineral Spirits (with < 0.1% Benzene)	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	
Titanium Dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	respirable particulate matter	(vacated) TWA: 10 mg/m <sup>3</sup>	TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine
	TWA: 2.5 mg/m <sup>3</sup> finescale	total dust	TWA: 0.3 mg/m <sup>3</sup> CIB 63
	respirable particulate matter		ultrafine, including engineered
			nanoscale

#### Appropriate engineering controls

Showers **Engineering controls** 

Eyewash stations

Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

**Respiratory protection** Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

# 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

AppearanceViscousColorWhite; Black

Odor Solvent (Mineral Spirits)

Odor threshold 1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine

potentially hazardous substances.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

**pH** Not applicable 7.0

pH (as aqueous solution)

None known

Melting point/freezing point No data available Melting Point is not applicable. Freezing points are

snov

Boiling point / boiling range > 154 °C / 309.2 °F

Flash point > 49.4444 °C / 121 °F Pensky-Martens Closed Cup (PMCC)

**Evaporation rate** 0.1 Butly acetate = 1

Flammability (solid, gas)

Flammability Limit in Air

Flammable above 105 degrees F and 40.5 degrees

C

Upper flammability limit: 7.0 Lower flammability limit: 1.6

Vapor pressure 0.3 (kPa) @ 20 °C

Vapor density 5.3 Where: Air = 1 at 68 degrees F (20 degrees C)

**Relative density** 1.01 Water = 1g/ml

Water solubility

No data available Insoluble

Reacts with water to form carbon dioxide

Solubility(ies)No data available.InsoluablePartition coefficientNo data available.No data available.Autoignition temperature330 °C / 626 °F

Autoignition temperature Decomposition temperature

Kinematic viscosity

**Dynamic viscosity** No data available. @ 25 °C

Other information

Explosive properties No information available Oxidizing properties No information available

Softening point Not applicable

Molecular weight N/A

VOC Content (%)

Density

Bulk density

Less than 300 g/l
~8.45 lb/gal
Not applicable

# 10. Stability and reactivity

**Reactivity** No information available.

**Chemical stability** Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

**Hazardous polymerization** Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Excessive heat.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

# 11. Toxicological information

### Information on likely routes of exposure

### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful

by inhalation. (based on components).

**Eye contact** Specific test data for the substance or mixture is not available. May cause irritation. Causes

serious eye irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness

or cracking. Causes skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

**Acute toxicity** Harmful by inhalation.

**Numerical measures of toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 5,394.90 mg/kg **ATEmix (dermal)** 99,999.00 mg/kg

ATEmix (inhalation-gas) 99,999.00 ppm ATEmix (inhalation-vapor) 11.00 mg/l ATEmix (inhalation-dust/mist) 6.82 mg/l

#### Unknown acute toxicity

97 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

**Component Information** 

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat)4 h
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Polyethylene homopolymer 9002-88-4	> 8 g/kg (Rat)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

**Respiratory or skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen

The table below indicates whether each agency has listed any ingredient as a carolingen.				
Chemical name	ACGIH	IARC	NTP	OSHA
Hydrated Aluminum-Magnesium	-	Group 2B	-	X
Silicate				
12174-11-7				
Titanium Dioxide	A3	Group 2B	-	X
13463-67-7		-		
Polyethylene homopolymer	-	Group 3	-	-
9002-88-4		·		

### Legend

**ACGIH (American Conference of Governmental Industrial Hygienists)** 

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

**Developmental Toxicity**None known for product as a whole.

**Teratogenicity** None known.

**STOT - single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

Target organ effects Kidney, Respiratory system, Eyes, Skin, Central nervous system, Lungs.

**Aspiration hazard** May be fatal if swallowed and enters airways.

Other adverse effects N/A.

Interactive effects No information available.

# 12. Ecological information

### **Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Solvent Naphtha	<del>-</del>	LC50: =9.22mg/L (96h,	-	EC50: =6.14mg/L (48h,
64742-95-6		Oncorhynchus mykiss)		Daphnia magna)

Persistence and degradability N/A.

**Bioaccumulation** There is no data for this product.

Other adverse effects No information available.

# 13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

# 14. Transport information

**DOT** DOT Ground: Not regulated if containers are less than119 gallons (450 liters).

TDG Not regulated.

MEX Not regulated.

IATA Not regulated.

**IMDG** Not regulated.

# 15. Regulatory information

### **International Inventories**

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Hydrocarbon Resin	68132-00-3	Present	Active
Solvent Naphtha	64742-95-6	Present	Active
Styrene/Butadiene Copolymer	66070-58-4	Present	Active
Hydrated Aluminum-Magnesium Silicate	12174-11-7	-	Unknown *
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	Present	Active
Titanium Dioxide	13463-67-7	Present	Active
Polyethylene homopolymer	9002-88-4	Present	Active
Solvent Blend	-	-	Unknown *

<sup>\*</sup>Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

**DSL/NDSL** All of the components of this product are listed on the DSL.

**EINECS/ELINCS** All components are listed.

**TCSI** Contact supplier for inventory compliance status.

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

### **US Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

### **US State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals:.

Chemical name		California Proposition 65	
	Hydrated Aluminum-Magnesium Silicate - 12174-11-7	Carcinogen	
	Titanium Dioxide - 13463-67-7	Carcinogen	

### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits (with < 0.1% Benzene)	X	X	X
8052-41-3			
Titanium Dioxide	X	X	X
13463-67-7			

#### U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

### 16. Other information

Health hazards 3 NFPA Flammability 2 Instability 0 Special hazards -Health hazards \* 3 Physical hazards 0 **HMIS** Flammability 2 Personal protection -Chronic Hazard Star Legend \* = Chronic Health Hazard

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Legend

SVHC: Substances of Very High Concern for Authorization: PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

### Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

STEL (Short Term Exposure Limit) TWA TWA (time-weighted average) STEL

Ceiling Maximum limit value Skin designation

Sensitizers

### Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

**Environmental Protection Agency** 

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Prepared By Lucas Technical Service Department.

Revision Date 31-Jan-2025

Revision Note N/A.

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.