



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 04-Feb-2025

Version 1

1. Identification

Product identifier

Product Name All Weather Roof Cement

Other means of identification

Product Code LUCAS 775

UN/ID no. 1993

Synonyms Grades 775S & 775W

Recommended use of the chemical and restrictions on use

Recommended Use Used to install, repair or rebuild roof flashings at parapet walls, gravel stops, stacks, vents, monitors and similar applications. Can be used with fiberglass, polyester fabrics or roll roofing for permanent repairs.

Restrictions on use For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Supplier Address

Manufacturer Address

R.M. Lucas Company
3211 S. Wood St
Chicago, Illinois 60608
(773) 523-4300

Emergency telephone number

Emergency Telephone Call CHEMTREC Day or Night:
Within USA and Canada: 1-800 424-9300

2. Hazard(s) identification

Classification

Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements



Danger

Hazard statements

Harmful in contact with skin.
Causes skin irritation.
Causes serious eye irritation.
May cause cancer.
May cause respiratory irritation. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/clothing and eye/face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water and soap.
Call a POISON CENTER or doctor if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Unknown acute toxicity

31.6 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

Other Information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Common name Flashing Cement.

Synonyms Grades 775S & 775W.

Chemical nature Organic solvents and additives.

Chemical name	CAS No.	Weight-%	Trade secret
Asphalt (at Ambient Temperature)	8052-42-4	40-60	*
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	20-30	*
Calcium Carbonate	471-34-1	10-30	*
Hydrated Aluminum-Magnesium Silicate	12174-11-7	0-10	*
Cellulose Fiber	9004-34-6	0-10	*
Asphalt, oxidized	64742-93-4	0-10	*
Solvent Naphtha	64742-95-6	0-10	*
Kaolin	1332-58-7	0-10	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	No information available.
Hazardous combustion products	Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.
Other information	Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid breathing vapors or mists. In case of insufficient ventilation, wear suitable respiratory equipment.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.
---------------------------	---

8. Exposure controls/personal protection

Control parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Asphalt (at Ambient Temperature) 8052-42-4	TWA: 0.5 mg/m ³ Benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Calcium Carbonate 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Hydrated Aluminum-Magnesium Silicate 12174-11-7	TWA: 1 mg/m ³ respirable particulate matter	-	-
Cellulose Fiber 9004-34-6	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ (vacated) STEL: 10 mg/m ³	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 1 mg/m ³
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

Biological occupational exposure limits

Chemical name	ACGIH
Asphalt (at Ambient Temperature) 8052-42-4	2.5 µg/L - urine (1-Hydroxypyrene with hydrolysis) - end of shift at end of workweek

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Respiratory protection	Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Paste / Gel Liquid
Appearance	Thick mastic
Color	Black
Odor	Solvent (Mineral Spirits)
Odor threshold	1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	7.0
pH (as aqueous solution)		None known
Melting point/freezing point	None / -70 None / -94	Melting Point is not applicable. Freezing points are shown.
Boiling point / boiling range	> 154 °C / 309.2 °F	
Flash point	> 40.5 °C / 104.90 °F	Setaflash
Evaporation rate	0.1	Butly acetate = 1
Flammability (solid, gas)		
Flammability Limit in Air		Flammable above 105 degrees F and 40.5 degrees C.
Upper flammability limit:	7.0	
Lower flammability limit:	1.6	
Vapor pressure	0.3 (kPa)	@ 20 °C
Vapor density	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
Relative density	1.09	Water = 1g/ml
Water solubility	No data available Insoluble	Reacts with water to form carbon dioxide
Solubility(ies)	No data available.	Insoluable
Partition coefficient	No data available.	No data available.
Autoignition temperature	330 °C / 626 °F	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	No data available.	@ 25 °C
Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	Not applicable	
Molecular weight	N/A	
VOC Content (%)	Less than 300 g/l	
Density	9.2 to 9.5 lb/gal	
Bulk density	Not applicable	

10. Stability and reactivity

Reactivity	No information available.
-------------------	---------------------------

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	Hazardous polymerization does not occur.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents.
Hazardous decomposition products	Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	---

<u>Acute toxicity</u>	Harmful by skin contact.
------------------------------	--------------------------

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5,105.90 mg/kg
ATEmix (dermal)	1,943.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	8.49 mg/l

Unknown acute toxicity

31.6 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt (at Ambient Temperature) 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat) 4 h

Calcium Carbonate 471-34-1	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
Cellulose Fiber 9004-34-6	> 5 g/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h
Asphalt, oxidized 64742-93-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Solvent Naphtha 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Hydrated Aluminum-Magnesium Silicate 12174-11-7	-	Group 2B	-	X
Cellulose Fiber 9004-34-6	-	-	Known	-
Asphalt, oxidized 64742-93-4	-	Group 2A	-	X

Legend

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

Developmental Toxicity None known for product as a whole.

Teratogenicity None known.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Target organ effects	Kidney, Respiratory system, Eyes, Skin, Central nervous system, Gastrointestinal tract (GI).
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	N/A.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Asphalt, oxidized 64742-93-4	EC50: =56mg/L (72h, Pseudokirchneriella subcapitata)	-	-	-
Solvent Naphtha 64742-95-6	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50: =6.14mg/L (48h, Daphnia magna)

Persistence and degradability N/A.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Asphalt (at Ambient Temperature) 8052-42-4	6

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

14. Transport information

DOT

UN/ID no. 1993
Hazard Class 3
Packing Group III

TDG

UN/ID no. NA 1993
Proper shipping name Combustible liquid, n.o.s
Hazard Class 3
Packing Group III

MEX
UN/ID no. Regulated Not regulated.
 NA 1993
Proper shipping name Combustible liquid, n.o.s.

ICAO (air)
UN/ID no. Regulated Not regulated.
 1993

IATA
UN number or ID number Regulated Not regulated.
 1993

IMDG
UN number or ID number Regulated Not regulated.
 1993

15. Regulatory information

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

Chemical name	CAS No.	Inventory Listing Status	Commercial Activity Designation
Asphalt (at Ambient Temperature)	8052-42-4	Present	Active
Mineral Spirits (with < 0.1% Benzene)	8052-41-3	Present	Active
Calcium Carbonate	471-34-1	Present	Active
Hydrated Aluminum-Magnesium Silicate	12174-11-7	-	Unknown *
Cellulose Fiber	9004-34-6	Present	Active
Asphalt, oxidized	64742-93-4	Present	Active
Solvent Naphtha	64742-95-6	Present	Active
Kaolin	1332-58-7	Present	Active

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL All of the components of this product are listed on the DSL.
EINECS/ELINCS All components are listed.
TCSI Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TCSI - Taiwan Chemical Substance Inventory

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Hydrated Aluminum-Magnesium Silicate - 12174-11-7	Carcinogen
Cellulose Fiber - 9004-34-6	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Asphalt (at Ambient Temperature) 8052-42-4	X	X	X
Mineral Spirits (with < 0.1% Benzene) 8052-41-3	X	X	X
Cellulose Fiber 9004-34-6	X	X	X
Asphalt, oxidized 64742-93-4	X	-	-
Kaolin 1332-58-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 2	Instability 0	Special hazards -
HMIS	Health hazards 2 *	Flammability 2	Physical hazards 0	Personal protection -
<i>Chronic Hazard Star Legend</i> * = Chronic Health Hazard				

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate
LC50: 50% Lethal Concentration
LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Prepared By	Lucas Technical Service Department.
Revision Date	04-Feb-2025
Revision Note	N/A.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.